# MICRO RING II™  – WALL OR CEILING SURFACE

**Project Name:** | **Fixture Type:**

**Fixture Code:** | **Quantities:**

## A. LUMINAIRE

**MRTC1C02** 2ft, 5000 lms    **MRTC1C03** 3ft, 7400 lms    **MRTC1C04** 4ft, 9500 lms    **MRTC1C05** 5ft, 12900 lms

**MRTC1C06** 6ft, 15200 lms

## B. EFFICIENCY

**EFF1** Standard efficiency [1]    **EFF2** High efficiency [2]

[1] Standard efficiency refers to Standard efficacy.
[2] High efficiency refers to High efficacy. This option is 52% more efficient than Standard efficiency.

## C. LUMENS

**LPF017** 175 lm/ft [1][2]    **LPF026** 260 lm/ft [1][2]    **LPF035** 350 lm/ft [1][2]    **LPF052** 525 lm/ft [1][2]

**LPF080** 800 lm/ft [2]

[1] Standard efficiency is available from 175 lm/ft to 525 lms/ft.
[2] High efficiency is available from 175 lms/ft to 800 lm/ft.

## D. CRI

**CR80** CRI 80+    **CR90** CRI 90+

## E. CCT

**CTA27** 2700K [1]    **CTA30** 3000K    **CTA35** 3500K    **CTA40** 4000K

[1] Longer than normal lead times may apply, consult factory.

## F. VOLTAGE

**V1** 120/277V    **V2** 240V [1]    **V3** 347V [2]    **V4** Low Voltage [3]

[1] Not available in North America.
[2] Available with DA01 only.
[3] V4 available with DA45 dimming only.

## G. DIMMING (REMOTE)

**DA01** 0-10V Dimming 1.0%    **DA20** DALI Dimming 0.1% [1]    **DA21** DALI Dimming 1.0% [1]    **DA45** PoE [2]

[1] Not available with V3.
[2] Available with V4 only.

## H. FINISH

**FA01** White    **FA02** Black Metallic - Textured    **FA20** Silver Metallic    **FA25** Gold Metallic - Textured

**FA27** Wood grain - Light Cherry [1]    **FA28** Wood grain - Dark Walnut [1]    **FA44** Midnight Blue Metallic - Textured    **FA45** Copper Metallic

**FA46** Charcoal Metallic - Textured    **FA47** Bronze Metallic - Textured    **FA52** Champagne Metallic    **FA53** Red Metallic - Textured

[1] Longer lead time may apply, consult factory.

# MICRO RING II™ - WALL OR CEILING SURFACE

**E0** Not required                    **E2** Emergency system - Remote

# MICRO RING II™  - WALL OR CEILING SURFACE

**DIMENSIONAL DIAGRAMS**

57mm/2.25"

25mm/1"

Diameter (A)