

MICRO RING II™ - WALL OR CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

MRTC1C02 2ft, 5000 lms
MRTC1C06 6ft, 15200 lms

MRTC1C03 3ft, 7400 lms

MRTC1C04 4ft, 9500 lms

MRTC1C05 5ft, 12900 lms

B. EFFICIENCY

EFF1 Standard efficiency ¹

EFF2 High efficiency ²

¹ Standard efficiency refers to Standard efficacy.

² High efficiency refers to High efficacy. This option is 52% more efficient than Standard efficiency.

C. LUMENS

LPF017 175 lm/ft ^{1 2}
LPF080 800 lm/ft ²

LPF026 260 lm/ft ^{1 2}

LPF035 350 lm/ft ^{1 2}

LPF052 525 lm/ft ^{1 2}

¹ Standard efficiency is available from 175 lm/ft to 525 lms/ft.

² High efficiency is available from 175 lms/ft to 800 lm/ft.

D. CRI

CR80 CRI 80+

CR90 CRI 90+

E. CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

F. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Available with DA01 only.

³ V4 available with DA45 dimming only.

G. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% ¹

DA45 PoE ²

¹ Not available with V3.

² Available with V4 only.

H. FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic

FA25 Gold Metallic - Textured

FA27 Wood grain - Light Cherry ¹

FA28 Wood grain - Dark Walnut ¹

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

¹ Longer lead time may apply, consult factory.

I. EMERGENCY

E0 Not required

E2 Emergency system - Remote



MICRO RING II™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

