


MICRO RING SE™ - WALL OR CEILING SURFACE



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

MRGC1C02 26" Inside ring

MRGC1C03 36" Inside ring

MRGC1C04 48" Inside ring

MRGC1C05 60" Inside ring

MRGC1C06 72" Inside ring

MRGC2C02 26" Outside ring

MRGC2C03 36" Outside ring

MRGC2C04 48" Outside ring

MRGC2C05 60" Outside ring

MRGC2C06 72" Outside ring

B. LUMENS/FT

LPF012 125 lm/ft ¹

LPF018 185 lm/ft ²

LPF025 250 lm/ft ³

¹ Based on 50% of total output.

² Based on 75% of total output.

³ 100% of total output.

C. CRI

CR80 CRI 80+

CR90 CRI 90+

D. CCT

CTA27 2700K ¹

CTA30 3000K

CTA35 3500K

CTA40 4000K

¹ Longer than normal lead times may apply, consult factory.

E. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

¹ Not available in North America.

² Available with DAO1 dimming only.

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%

DA20 DALI Dimming 0.1%

DA21 DALI Dimming 1.0%

G. FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

H. EMERGENCY

E0 Not required

E2 Emergency system - Remote



MICRO RING SE™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

