

# MICRO RING™ - WALL OR CEILING SURFACE



Project Name:

Fixture Type:

Fixture Code:

Quantities:

## A. LUMINAIRE

**MRRC1C02** 2ft, 4700 lms  
**MRRC1C06** 6ft, 14100 lms

**MRRC1C03** 3ft, 6900 lms

**MRRC1C04** 4ft, 8800 lms

**MRRC1C05** 5ft, 12000 lms

## B. EFFICIENCY

**EFF1** Standard efficiency <sup>1</sup>

**EFF2** High efficiency <sup>2</sup>

<sup>1</sup> Standard efficiency refers to Standard efficacy.

<sup>2</sup> High efficiency refers to High efficacy. This option is 52% more efficient than Standard efficiency.

## C. LUMENS

**LPF017** 175 lm/ft <sup>1 2</sup>  
**LPF075** 750 lm/ft <sup>2</sup>

**LPF026** 260 lm/ft <sup>1 2</sup>

**LPF035** 350 lm/ft <sup>1 2</sup>

**LPF052** 525 lm/ft <sup>2</sup>

<sup>1</sup> Standard efficiency is available from 175 lm/ft to 350 lm/ft.

<sup>2</sup> High efficiency is available from 175 lm/ft to 750 lm/ft.

## D. CRI

**CR80** CRI 80+

**CR90** CRI 90+

## E. CCT

**CTA27** 2700K

**CTA30** 3000K

**CTA35** 3500K

**CTA40** 4000K

## F. VOLTAGE

**V1** 120/277V

**V2** 240V <sup>1</sup>

**V3** 347V <sup>2</sup>

**V4** Low Voltage <sup>3</sup>

<sup>1</sup> Not available in North America.

<sup>2</sup> Available with DA01 dimming only.

<sup>3</sup> Available with DA45 dimming only.

## G. DIMMING (REMOTE)

**DA01** 0-10V Dimming 1.0%

**DA20** DALI Dimming 0.1% <sup>1</sup>

**DA21** DALI Dimming 1.0% <sup>1</sup>

**DA45** PoE <sup>2</sup>

<sup>1</sup> Not available with V3.

<sup>2</sup> Available with V4 only.

## H. FINISH

**FA01** White

**FA02** Black Metallic - Textured

**FA20** Silver Metallic - Textured

**FA25** Gold Metallic - Textured

**FA44** Midnight Blue Metallic - Textured

**FA45** Copper Metallic

**FA46** Charcoal Metallic - Textured

**FA47** Bronze Metallic - Textured

**FA52** Champagne Metallic

**FA53** Red Metallic - Textured

## I. EMERGENCY

**E0** Not required

**E2** Emergency system - Remote



# MICRO RING™ - WALL OR CEILING SURFACE

## DIMENSIONAL DIAGRAMS

