

MICRO RING™ - WALL OR CEILING SURFACE



Project Name:	Fixture Type:
Fixture Code:	Quantities:

A. LUMINAIRE

MRRC1C02 2ft, 4700 lms	MRRC1C03 3ft, 6900 lms	MRRC1C04 4ft, 8800 lms	MRRC1C05 5ft, 12000 lms
MRRC1C06 6ft, 14100 lms			

B. EFFICIENCY

EFF1 Standard efficiency ¹	EFF2 High efficiency ²
---------------------------------------	-----------------------------------

¹ Standard efficiency refers to Standard efficacy.
² High efficiency refers to High efficacy. This option is 52% more efficient that Standard efficiency.

C. LUMENS

LPF017 175 lm/ft ^{1 2}	LPF026 260 lm/ft ^{1 2 3}	LPF035 350 lm/ft ^{1 2 4}	LPF052 525 lm/ft ^{2 5}
LPF075 750 lm/ft ^{2 6}			

¹ Standard efficiency is available from 175 lm/ft to 350 lm/ft.
² High efficiency is available from 175 lm/ft to 750 lm/ft.

D. CRI

CR80 CRI 80+	CR90 CRI 90+
--------------	--------------

E. CCT

CTA27 2700K	CTA30 3000K	CTA35 3500K	CTA40 4000K
-------------	-------------	-------------	-------------

F. VOLTAGE

V1 120/277V	V2 240V ¹	V3 347V ²	V4 Low Voltage ³
-------------	----------------------	----------------------	-----------------------------

¹ Not available in North America.
² Available with DA01 dimming only.
³ Available with DA45 dimming only.

G. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%	DA20 DALI Dimming 0.1% ¹	DA21 DALI Dimming 1.0% ¹	DA45 PoE ²
-------------------------	-------------------------------------	-------------------------------------	-----------------------

¹ Not available with V3.
² Available with V4 only.

H. FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured
FA52 Champagne Metallic	FA53 Red Metallic - Textured		

I. EMERGENCY

E0 Not required	E2 Emergency system - Remote
-----------------	------------------------------

MICRO RING™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

