

MICRO STRAIGHT II™ - SUSPENDED



Project Name:	Fixture Type:
Fixture Code:	Quantities:

A. LUMINAIRE

AT3 36", Direct, 1510 lms	AT4 48", Direct, 2068 lms	AT5 60", Direct, 2647 lms	AT6 72", Direct, 3309 lms
AT7 84", Direct, 3805 lms	AT8 96", Direct, 4343 lms	AT11 36", Direct/Indirect, 3069 lms	AT12 48", Direct/Indirect, 4205 lms
AT13 60", Direct/Indirect, 5382 lms	AT14 72", Direct/Indirect, 6727 lms	AT15 84", Direct/Indirect, 7736 lms	AT16 96", Direct/Indirect, 8830 lms

Direct lms/ft = 520, Direct/Indirect lms/ft = 1060.

B. CCT/COLOR (DIRECT)

J1 2700K (min 80 CRI)	J2 3000K (min 80 CRI)	J3 3500K (min 80 CRI)	J4 4000K (min 80 CRI)
J7 Red	J8 Green	J9 Blue	

C. CCT/COLOR (INDIRECT)

K0 Indirect CCT/Color not required	K1 2700K (min 80 CRI)	K2 3000K (min 80 CRI)	K3 3500K (min 80 CRI)
K4 4000K (min 80 CRI)	K7 Red	K8 Green	K9 Blue

D. UPLIGHT DIFFUSER

U0 Uplight diffuser not required	U1 Clear diffuser	U2 Opal diffuser	
---	--------------------------	-------------------------	--

E. DIMMING

D1 0-10V Dimming (1.0%)	D4 DALI Dimming (0.1%)	D5 DALI Dimming (1.0%)	DA45 PoE
--------------------------------	-------------------------------	-------------------------------	-----------------

Remote drivers only. D4 for use in North America only.
DA45 must be used with EV only.

F. FINISH

F1 White	F2 Black Metallic Textured	F20 Silver Metallic Textured	F27 Wood grain - Light Cherry ¹
F28 Wood grain - Dark Walnut ¹	FA25 Gold Metallic - Textured	FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic
FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic	FA53 Red Metallic - Textured

Note: The canopy will be white for fixtures with the wood grain finishes F27 & F28.
¹ Available upon request and longer than normal lead times may apply, consult factory.

G. LUMEN OUTPUT

L0 100% of standard output	L1 Lumen & wattage reduction to approximately 75% of standard output	L2 Lumen & wattage reduction to approximately 50% of standard output	L3 Lumen & wattage reduction to approximately 25% of standard output
-----------------------------------	---	---	---

L3 is not available with AT3, AT4, AT5 & AT11. L2 is not available with AT3. Custom reduction percentages available upon request.

H. OPTIONAL LOW VOLTAGE

EV Low Voltage
To be used with DA45 only.

MICRO STRAIGHT II™ - SUSPENDED

DIMENSIONAL DIAGRAMS

