


MICRO TRIANGLE SE™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MICRO TRIANGLE SE™ - SUSPENDED



MICRO TRIANGLE SE™ - SUSPENDED

The triangular shape is a powerful way to create an edgy and energetic aesthetic. With a super-slim 1" profile and 3 sizes ranging from 2' to 4', **MICRO TRIANGLE SE** is ideal for offsetting symmetrical layouts. The light uniquely emits from the inner side of the frame and can be coordinated with MICRO TRIANGLE II which offers direct/indirect light. For a whimsical style, combine **MICRO TRIANGLE** with MICRO RING or MICRO QUAD. Available in a multitude of distinct finishes, this statement piece adds refinement and sophistication to your space.

GENERAL SPECIFICATION

Body

Aluminum, Equilateral Triangle

Suspension

Stainless steel cables.

Remote Mounting Of Drivers

Wire size 18 AWG - max distance (from fixture to drivers) 40'; wire size 16 AWG - max distance 60'; wire size 14 AWG - max distance 90'. Drivers must be accessible after installation. For longer remote distances, consult factory.

PoE

Micro Triangle SE can integrate into your data network via Power over Ethernet (PoE) connectivity.

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI) for White LEDs only.

Sensors

Consult factory regarding sensor compatibility.

Reported L70 @25°C (77°F)

> 60,000 hrs.

Seismic Bracing

Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

Finish

Powder coated for standard finishes (black, Silver Metallic & white).

Power cable

Silver braided.

Drivers

HPF electronic drivers for 120-277V (EU-240V). Drivers are either remote mounted or integral to the canopy depending on the size of the fixture.

Mechanical

Luminaires attached directly to the J box (by others - North America only).

CRI

Fixture supplied at 80 CRI, 90 CRI available upon request.


Lens

Frosted acrylic.

Approvals

Damp Rated.


OPTICS & FEATURES



Suspended Inside



Acoustic



General Diffuse



Declare



PoE



MICRO TRIANGLE SE™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

984210 24", Inside, 2321 lms	984220 36", Inside, 3633 lms	984230 48", Inside, 4799 lms
-------------------------------------	-------------------------------------	-------------------------------------

B. CCT/COLOR

27 2700K (min 80 CRI) RD Red	30 3000K (min 80 CRI) GN Green	35 3500K (min 80 CRI) BL Blue	40 4000K (min 80 CRI)
---	---	--	------------------------------

CR90 (CRI 90+) available upon request, consult factory.

C. DIMMING OPTION (REMOTE ONLY)

D1 0-10V Dimming 1.0%	D4 DALI Dimming 0.1%	D5 DALI Dimming 1.0%	DA45 PoE
------------------------------	-----------------------------	-----------------------------	-----------------

DA45 must be used with EV only.

D. SUSPENSION

S1 Vertical, Remote Driver	S2 Hub, Remote Driver	S3 Vertical, Driver Integral to Canopy	S4 Hub, Driver Integral to Canopy
-----------------------------------	------------------------------	---	--

E. FINISH

WH White	BL Black Metallic Textured	MS Silver Metallic Textured	Z1 Wood grain - Light Cherry ¹
Z2 Wood grain - Dark Walnut ¹	Z3 Wood grain - White Oak ¹	FA25 Gold Metallic - Textured	FA44 Midnight Blue Metallic - Textured
FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic

Note: The canopy will be white for fixtures with the wood grain finishes Z1 & Z2.

¹ Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

F. LUMEN & WATTAGE REDUCTION

PRO Lumen & Wattage Reduction to approximately 25% of standard output	PR1 Lumen & Wattage Reduction to approximately 50% of standard Output	PR2 Lumen & Wattage Reduction to approximately 75% of standard Output
--	--	--

PRO not available for 984210. Note: Custom reduction percentages available upon request.

G. ACOUSTIC PANEL COLOR

AP00 Not required	AP02 Citrus	AP04 White	AP08 Red Coffee
AP11 Light Gray	AP13 Apple Green	AP22 Blue	AP26 Sesame Gray
AP27 Black	AP47 Navy Peony	AP60 Pure Red	AP73 Cloudburst
AP89 Douglas Fir	APW01 Oak		

For accompanying non-illuminating acoustic panels, see our Acoustic Circles, Quads, Triangles, and Ellipse spec pages.

Contact factory for larger sizes and additional colors.

H. OPTIONAL LOW VOLTAGE

EV Low Voltage

To be used with DA45 only.


MICRO TRIANGLE SE™ - SUSPENDED

TECHNICAL DATA


LUMINAIRE

Code	984210	984220	984230
Length	24"	36"	48"
Power (LED)	20W	30W	40W
Light Direction	Inside	Inside	Inside
Delivered lms	2321	3633	4799
LPW	116	122	120


FINISH




White




Black Metallic Textured




Silver Metallic Textured




Wood grain - Light Cherry ¹




Wood grain - Dark Walnut ¹




Wood grain - White Oak ¹




Gold Metallic - Textured




Midnight Blue Metallic - Textured




Copper Metallic



Charcoal Metallic - Textured



Bronze Metallic - Textured



Champagne Metallic

Note: The canopy will be white for fixtures with the wood grain finishes Z1 & Z2.

¹ Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

ACOUSTIC PANEL COLOR



Not required



Citrus




White




Red Coffee




Light Gray



Apple Green



Blue



Sesame Gray



Black



Navy Peony



Pure Red



Cloudburst



Douglas Fir



Oak

For accompanying non-illuminating acoustic panels, see our Acoustic Circles, Quads, Triangles, and Ellipse spec pages.

Contact factory for larger sizes and additional colors.

MICRO TRIANGLE SE™ - SUSPENDED


APPROVALS




MICRO TRIANGLE SE™ - SUSPENDED

DIMENSIONAL DIAGRAMS


S1
Vertical - Remote Driver




S2
Hub - Remote Driver



S3
Vertical - Integral Driver



S4
Hub - Integral Driver



MICRO TRIANGLE SE™ - SUSPENDED

Power Over Suspension

