

MIDI ARC RING™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MIDI ARC RING™ - SUSPENDED



MIDI ARC RING™ - SUSPENDED

The curved edge softens the classic architectural form and raises the impact of distinctive spaces. Giving more curve to the curve, the smooth edges of **MIDI ARC** add a sleek and enticing appearance.

GENERAL SPECIFICATION

Finish

Powder coated or polished.

Power cable

Silver braided.

Remote emergency

Emergency option provides a 1.5 hour (3hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch. Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

Drivers

HPF electronic drivers for 120-277V (EU-240V). Drivers are either remote mounted or integral to the canopy depending on the size of the fixture.

Acoustic Panels NRC Rating

0.80

Acoustic Panels Material

100% recycled polyester fiber (PET).

Mechanical

Luminaires mount directly over J box (by others).

Sensors

Consult factory regarding sensor compatibility.

Approvals

Damp Rated.

Seismic Bracing

Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

Suspension

Steel cables.

Diffuser

Opal acrylic.

Remote mounting of drivers

Wire size 18 AWG - max distance (from fixture to drivers) 40' 12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation.

PoE

Midi Arch Ring can integrate into your data network via Power over Ethernet (PoE) connectivity.

Acoustic Panels Fire Rating

ASTM E84-2018 Class A.

Acoustic Panels Thickness

12mm (0.5")

Delivered lumens

Delivered lumens & LPW based on 4000K CRI 80+

L70 @25°C (77°F)

> 60,000 hrs.

Design

US Pat. No. D898,979.


Acoustic Panel Maintenance

Durable and easy to maintain. Dust regularly and clean marks with mild detergent, rinse, and blot.

OPTICS & FEATURES



Suspended Direct



Suspended Direct/Indirect



Declare



PoE



MIDI ARC RING™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

MARP1P04 48" Direct, 4100 lms	MARP1P05 60" Direct, 5100 lms	MARP1P06 72" Direct, 6100 lms	MARP1P07 84" Direct, 7200 lms
MARP2P04 48" Direct/Indirect, 8200 lms	MARP2P05 60" Direct/Indirect, 10200 lms	MARP2P06 72" Direct/Indirect, 12200 lms	MARP2P07 84" Direct/Indirect, 14400 lms

Lumens shown are at max value.

B. LUMENS (DIRECT)

LPF015 150 lms/ft ¹	LPF022 225 lms/ft ²	LPF030 300 lms/ft ³
---------------------------------------	---------------------------------------	---------------------------------------

¹ Based on 50% of total output

² Based on 75% of total output

³ 100% of total output

C. LUMENS (INDIRECT)

LPG000 Not required	LPG015 150 lms/ft ¹	LPG022 225 lms/ft ²	LPG030 300 lms/ft ³
----------------------------	---------------------------------------	---------------------------------------	---------------------------------------

Values shown are nominal.

¹ Based on 50% of total output

² Based on 75% of total output

³ 100% of total output

D. CRI

CR80 CRI 80+	CR90 CRI 90+
---------------------	---------------------

E. CCT (DIRECT)

CTA27 2700K	CTA30 3000K	CTA35 3500K	CTA40 4000K
--------------------	--------------------	--------------------	--------------------

F. CCT (INDIRECT)

CTB00 Not required	CTB27 2700K	CTB30 3000K	CTB35 3500K
CTB40 4000K			

G. VOLTAGE

V1 120/277V	V2 240V ¹
--------------------	-----------------------------

¹ Not available in North America

H. SUSPENSION

SS1 Vertical, Remote driver	SS2 Hub, Remote driver ^{1 2}	SS3 Vertical, Driver Integral to Canopy ²	SS4 Hub, Driver Integral to Canopy ^{1 2}
------------------------------------	--	---	--

¹ Not available with MARP1P06 and MARP1P07

² Not available with MARP2P06 and MARP2P07

I. DIMMING

DA01 0-10V Dimming 1.0%	DA02 0-10V Dimming 0.1% ¹	DA20 DALI Dimming 0.1% ¹	DA21 DALI Dimming 1.0% ¹
DA30 DSI/switchDim ²			

¹ Not available with MARP2P05, MARP2P06 and MARP2P07.

² Not available in North America.

MIDI ARC RING™ - SUSPENDED

J. FIXTURE FINISH

FA56 White - Gloss	FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured
FA25 Gold Metallic - Textured	FA42 Polished Aluminum - Mirror finish	FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic
FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic	FA53 Red Metallic - Textured

K. CANOPY FINISH

CF56 White - Gloss	CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured
CF25 Gold Metallic - Textured	CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured
CF47 Bronze Metallic - Textured	CF52 Champagne Metallic	CF53 Red Metallic - Textured	

L. EMERGENCY

E0 Not required	E2 Emergency system - Remote
------------------------	-------------------------------------

M. CIRCUIT

CS1 Single circuit	CS2 Dual circuit
---------------------------	-------------------------

MIDI ARC RING™ - SUSPENDED

TECHNICAL DATA


LUMINAIRE

Lumens shown are at max value.


Code	MARP1P04	MARP1P05	MARP1P06	MARP1P07	MARP2P04	MARP2P05
Diameter (A)	48"	60"	72"	84"	48"	60"
Lm/ft Down	300	300	300	300	300	300
Lm/ft Up					300	300
Lms Down	4100	5100	6100	7200	4100	5100
Lms Up					4100	5100
Wattage	40W	54W	64W	76W	86W	108W
LPW	95	95	95	95	95	95
Suspension Points	3	3	4	4	3	3

Code	MARP2P06	MARP2P07
Diameter (A)	72"	84"
Lm/ft Down	300	300
Lm/ft Up	300	300
Lms Down	6100	7200
Lms Up	6100	7200
Wattage	128W	152W
LPW	95	95
Suspension Points	4	4


FIXTURE FINISH




White - Gloss




White




Black Metallic -
Textured




Silver Metallic -
Textured




Gold Metallic -
Textured




Polished Aluminum -
Mirror finish




Midnight Blue Metallic -
Textured




Copper Metallic




Charcoal Metallic -
Textured



Bronze Metallic -
Textured














Champagne Metallic



Red Metallic -
Textured

MIDI ARC RING™ - SUSPENDED

CANOPY FINISH

							
White - Gloss	White	Black Metallic - Textured	Silver Metallic - Textured	Gold Metallic - Textured	Midnight Blue Metallic - Textured	Copper Metallic	Charcoal Metallic - Textured
							
Bronze Metallic - Textured	Champagne Metallic	Red Metallic - Textured					


APPROVALS

     IP20


MIDI ARC RING™ - SUSPENDED

DIMENSIONAL DIAGRAMS


SS1
Vertical - Remote Driver




SS2
Hub - Remote Driver




SS2
Hub - Remote Driver




SS4
Hub - Integral Driver



MIDI ARC RING™ - SUSPENDED



ISOMETRIC VIEW - 3 Suspension Points
48" [1219mm]
60" [1524mm]



ISOMETRIC VIEW - 4 Suspension Points
72" [1829mm]
84" [2134mm]