

MICRO SQ II™ - WALL OR CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



MICRO SQ II™ - WALL OR CEILING SURFACE

GENERAL SPECIFICATION

Body

Aluminium.

Lens

Frosted Polycarbonate.

L70 @25°C

> 50,000 hrs.

Finish

Powder coated.

Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers)40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


OPTICS & FEATURES




Ceiling Direct/Indirect



Ceiling Direct



Wall Direct/Indirect



Wall Direct



MICRO SQ II™ - WALL OR CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

983405 983405
983440 983440
983530 983530

983410 983410
983505 983505
983540 983540

983420 983420
983510 983510

983430 983430
983520 983520

B. CCT/COLOR (DIRECT)

D30 3000K (min 80 CRI)
DGN Green

D35 3500K (min 80 CRI)
DBL Blue

D40 4000K (min 80 CRI)

DRD Red

C. CCT/COLOR (INDIRECT)

N30 3000K (min 80 CRI)
NGN Green

N35 3500K (min 80 CRI)
NBL Blue

N40 4000K (min 80 CRI)

NRD Red

D. FINISH

BL Black
Z2 Wood Grain - Dark Walnut

MS Silver Metallic

WH White

Z1 Wood Grain - Light Cherry

TECHNICAL DATA

LUMINAIRE

Code	983405	983410	983420	983430	983440	983505
Diameter (A)	24"	35"	48"	60"	73"	24"
Power (LED)	26W	39W	51W	70W	83W	31W
Light Distribution	Direct	Direct	Direct	Direct	Direct	Direct/Indirect
Delivered lms	3131	4689	6225	8574	10102	3767
LPW	120	120	122	122	122	122
Code	983510	983520	983530	983540		
Diameter (A)	35"	48"	60"	73"		
Power (LED)	47W	62W	84W	100W		
Light Distribution	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect		
Delivered lms	5628	7469	10292	12125		
LPW	120	120	123	121		

APPROVALS



IP20



MICRO SQ II™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

