

# MICRO SQ II™ - WALL OR CEILING SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# MICRO SQ II™ - WALL OR CEILING SURFACE

## GENERAL SPECIFICATION

### Body

Aluminium.

### Lens

Frosted Polycarbonate.

### L70 @25°C

> 50,000 hrs.

### Finish

Powder coated.

### Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers)40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


## OPTICS & FEATURES




Ceiling Direct/Indirect



Ceiling Direct



Wall Direct/Indirect



Wall Direct

# MICRO SQ II™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

<b>983405</b> 983405	<b>983410</b> 983410	<b>983420</b> 983420	<b>983430</b> 983430
<b>983440</b> 983440	<b>983505</b> 983505	<b>983510</b> 983510	<b>983520</b> 983520
<b>983530</b> 983530	<b>983540</b> 983540		

### B. CCT/COLOR (DIRECT)

<b>D30</b> 3000K (min 80 CRI)	<b>D35</b> 3500K (min 80 CRI)	<b>D40</b> 4000K (min 80 CRI)	<b>DRD</b> Red
<b>DGN</b> Green	<b>DBL</b> Blue		

### C. CCT/COLOR (INDIRECT)

<b>N30</b> 3000K (min 80 CRI)	<b>N35</b> 3500K (min 80 CRI)	<b>N40</b> 4000K (min 80 CRI)	<b>NRD</b> Red
<b>NGN</b> Green	<b>NBL</b> Blue		

### D. FINISH

<b>BL</b> Black	<b>MS</b> Silver Metallic	<b>WH</b> White	<b>Z1</b> Wood Grain - Light Cherry
<b>Z2</b> Wood Grain - Dark Walnut			

## TECHNICAL DATA

### LUMINAIRE

Code	<b>983405</b>	<b>983410</b>	<b>983420</b>	<b>983430</b>	<b>983440</b>	<b>983505</b>
<b>Diameter (A)</b>	24"	35"	48"	60"	73"	24"
<b>Power (LED)</b>	26W	39W	51W	70W	83W	31W
<b>Light Distribution</b>	Direct	Direct	Direct	Direct	Direct	Direct/Indirect
<b>Delivered lms</b>	3131	4689	6225	8574	10102	3767
<b>LPW</b>	120	120	122	122	122	122

Code	<b>983510</b>	<b>983520</b>	<b>983530</b>	<b>983540</b>
<b>Diameter (A)</b>	35"	48"	60"	73"
<b>Power (LED)</b>	47W	62W	84W	100W
<b>Light Distribution</b>	Direct/Indirect	Direct/Indirect	Direct/Indirect	Direct/Indirect
<b>Delivered lms</b>	5628	7469	10292	12125
<b>LPW</b>	120	120	123	121

## APPROVALS



# MICRO SQ II™ - WALL OR CEILING SURFACE

## DIMENSIONAL DIAGRAMS

