MICRO TRIANGLE II - WALL OR CEILING SURFACE



Project Name: Fixture Type:

Fixture Code: Quantities:

A. LUMINAIRE

MTTC1C24 2ft Direct, 2600lms
MTTC1C72 6ft Direct, 7800lms

MTTC1C36 3ft Direct, 3900lms

MTTC1C48 4ft Direct, 5100lms

MTTC1C60 5ft Direct, 6500lms

B. LUMENS/FT

LPF021 215 lm/ft ¹

LPF032 320 lm/ft 2

LPF043 430 lm/ft 3

C. CRI

CR80 CRI 80+

CR90 CRI 90+

D. CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

E. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ² V4 Low Voltage ³

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% 1

DA45 PoE²

G. FINISH

FA01 White **FA27** Wood grain - Light Cherry ¹ **FA46** Charcoal Metallic - Textured **FA02** Black Metallic - Textured **FA28** Wood grain - Dark Walnut ¹ **FA47** Bronze Metallic - Textured

FA20 Silver Metallic - Textured
FA44 Midnight Blue Metallic - Textured
FA52 Champagne Metallic

FA25 Gold Metallic - Textured FA45 Copper Metallic FA53 Red Metallic - Textured

H. EMERGENCY

EO Not required

E2 Emergency system - Remote

¹ Based of 50% of total output.

² Based on 75% of total output.

³ 100% of total output.

¹ Not available in North America.

² Available with DA01 dimming only.

³ Available with DA45 dimming only.

¹ Not available with V3.

² Available with V4 only.

¹ Longer than normal lead times may apply, consult factory.

MICRO TRIANGLE II - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS



