

MICRO TRIANGLE II - WALL OR CEILING SURFACE



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

MTTC1C24 2ft Direct, 2600lms
MTTC1C72 6ft Direct, 7800lms

MTTC1C36 3ft Direct, 3900lms

MTTC1C48 4ft Direct, 5100lms

MTTC1C60 5ft Direct, 6500lms

B. LUMENS/FT

LPF021 215 lm/ft¹

LPF032 320 lm/ft²

LPF043 430 lm/ft³

¹ Based of 50% of total output.

² Based on 75% of total output.

³ 100% of total output.

C. CRI

CR80 CRI 80+

CR90 CRI 90+

D. CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

E. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V²

V4 Low Voltage³

¹ Not available in North America.

² Available with DA01 dimming only.

³ Available with DA45 dimming only.

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

DA45 PoE²

¹ Not available with V3.

² Available with V4 only.

G. FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA25 Gold Metallic - Textured

FA27 Wood grain - Light Cherry¹

FA28 Wood grain - Dark Walnut¹

FA44 Midnight Blue Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

H. EMERGENCY

E0 Not required

E2 Emergency system - Remote



MICRO TRIANGLE II - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

