





MICRO TRIANGLE SE™ - WALL OR CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



MICRO TRIANGLE SE™ - WALL OR CEILING SURFACE



MICRO TRIANGLE SE™ - WALL OR CEILING SURFACE

The triangular shape is a powerful way to create an edgy and energetic aesthetic. With a super-slim 1" profile and 3 sizes ranging from 2' to 4', **MICRO TRIANGLE SE** is ideal for offsetting symmetrical layouts. The light uniquely emits from the inner side of the frame and can be coordinated with MICRO TRIANGLE II which offers direct/indirect light. For a whimsical style, combine **MICRO TRIANGLE** with MICRO RING or MICRO QUAD. Available in a multitude of distinct finishes, this statement piece adds refinement and sophistication to your space.

GENERAL SPECIFICATION

Body

Aluminium, Equilateral Triangle

Lens

Frosted acrylic.

Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V). Wire size 18 AWG - max distance (from fixture to drivers) 40' 12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation. The driver is integral to the fixture canopy or remote mount depending on size of fixture. For longer remote distances, consult factory.

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

Approvals

Damp Rated.

Finish

Powder coated.

Sensors

Consult factory regarding sensor compatibility.


PoE

Micro Triangle SE can integrate into your data network via Power over Ethernet (PoE) connectivity.

Reported L70 @25°C (77°F)

> 60,000 hrs.

OPTICS & FEATURES



Ceiling Inside



Wall Inside



General Diffuse



Declare



PoE



MICRO TRIANGLE SE™ - WALL OR CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

MTEC1C02 2ft Inside, 2300 lms	MTEC1C03 3ft Inside, 3600 lms	MTEC1C04 4ft Inside, 4800 lms
--------------------------------------	--------------------------------------	--------------------------------------

B. LUMENS

LPF020 200 lm/ft ¹	LPF030 300 lm/ft ²	LPF040 400 lm/ft ³
--------------------------------------	--------------------------------------	--------------------------------------

¹ Based of 50% of total output.
² Based on 75% of total output.
³ 100% of total output.

C. CRI

CR80 CRI 80+	CR90 CRI 90+
---------------------	---------------------

D. CCT

CTA27 2700K	CTA30 3000K	CTA35 3500K	CTA40 4000K
--------------------	--------------------	--------------------	--------------------

E. VOLTAGE

V1 120/277V	V2 240V ¹	V3 347V ²	V4 Low voltage ³
--------------------	-----------------------------	-----------------------------	------------------------------------

¹ Not available in North America.
² Available with DA01 dimming only.
³ Available with DA45 dimming only.

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%	DA20 DALI Dimming 0.1% ¹	DA21 DALI Dimming 1.0% ¹	DA45 PoE ²
--------------------------------	--	--	------------------------------

G. FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic	FA25 Gold Metallic - Textured
FA27 Wood grain - Light Cherry ¹	FA28 Wood grain - Dark Walnut ¹	FA30 Wood grain - White Oak ¹	FA44 Midnight Blue Metallic - Textured
FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured	FA52 Champagne Metallic

¹ Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

H. SURFACE MOUNTING KIT

MK1 Surface mounting kit 1.25" extension c/w 3 spacers ¹	MK2 Surface mounting kit 2.75" extension c/w 3 spacers ²
--	--

¹ Standard.
² Extra length optional.

I. EMERGENCY

E0 Not required	E2 Emergency system - Remote
------------------------	-------------------------------------


MICRO TRIANGLE SE™ - WALL OR CEILING SURFACE

TECHNICAL DATA


LUMINAIRE

Code	MTEC1C02	MTEC1C03	MTEC1C04
Length	2ft	3ft	4ft
Light Direction	Inside	Inside	Inside
Wattage	20	30	40
Delivered lms	2300	3600	4800
LPW	116	122	120


FINISH




White




Black Metallic -
Textured




Silver Metallic




Gold Metallic -
Textured




Wood grain - Light
Cherry¹




Wood grain - Dark
Walnut¹




Wood grain - White
Oak¹




Midnight Blue Metallic -
Textured




Copper Metallic



Charcoal Metallic -
Textured



Bronze Metallic -
Textured



Champagne Metallic

¹ Wood grain finishes may incur longer lead times and setup charges. Consult factory for details.

APPROVALS

ADA



CE



DAMP
LOCATION



IP20

MICRO TRIANGLE SE™ - WALL OR CEILING SURFACE

DIMENSIONAL DIAGRAMS

