

ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

GENERAL SPECIFICATION

Housing

Die-cast and extruded aluminum.

Lens

Clear glass.

Reflector

High purity aluminum, silver anodized.

Drivers

HPF, electronic for 120-277V (EU-240V). Dimming 0-10V.

Weight

Maximum 4Kg/8.8lb.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

External Screws

Stainless steel.

Gaskets

One piece silicone.

Finish

Silver powder coated light gray or black powder coated as standard.

Minimum Starting Temperature

-30°C for LEDs.

Mechanical

Mounts directly over an electrical junction box (by others - Noth America only).

Mounting hardware (by others).

OPTICS & FEATURES



Ext-Ceiling/Canopy



10°



35°

ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

HOW TO ORDER

A. LUMINAIRE

267133 267133

267143 267143

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

GR Light Gray

D. OPTIONS

DB Dimming (0-10V, 10%)

TECHNICAL DATA

LUMINAIRE

Code	267133	267143
Power (LED)	14W	14W
Beam	10°	35°
Delivered lms	1049	1049

APPROVALS



ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

DIMENSIONAL DIAGRAMS

