

# ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

## GENERAL SPECIFICATION

### Housing

Die-cast and extruded aluminum.

### Lens

Clear glass.

### Reflector

High purity aluminum, silver anodized.

### Drivers

HPF, electronic for 120-277V (EU-240V). Dimming 0-10V.

### Weight

Maximum 4Kg/8.8lb.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### External Screws

Stainless steel.

### Gaskets

One piece silicone.

### Finish

Silver powder coated light gray or black powder coated as standard.

### Minimum Starting Temperature

-30°C for LEDs.

### Mechanical

Mounts directly over an electrical junction box (by others - Noth America only).

Mounting hardware (by others).

## MOUNTING & OPTICS



Ext-Ceiling/Canopy



10°



35°

# ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**267133** 267133

**267143** 267143

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**GR** Light Gray

### D. OPTIONS

**DB** Dimming (0-10V, 10%)

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>267133</b>	<b>267143</b>
<b>Power (LED)</b>	14W	14W
<b>Beam</b>	10°	35°
<b>Delivered lms</b>	1049	1049

## APPROVALS



# ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

## DIMENSIONAL DIAGRAMS

