

ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 4

ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

GENERAL SPECIFICATION

Housing

Die-cast and extruded aluminum.

External Screws

Stainless steel.

Lens

Clear glass.

Gaskets

One piece silicone.

Reflector

High purity aluminum, silver anodized.

Finish

Silver powder coated light gray or black powder coated as standard.

Drivers

HPF, electronic for 120-277V (EU-240V). Dimming 0-10V.

Minimum Starting Temperature

-30°C for LEDs.

Weight

Maximum 4Kg/8.8lb.

Mechanical


Mounts directly over an electrical junction box (by others - North America only).

Mounting hardware (by others).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Ext-Ceiling/Canopy

10°

35°



ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

HOW TO ORDER

A. LUMINAIRE

267133 267133

267143 267143

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

GR Light Gray

D. OPTIONS

DB Dimming (0-10V, 10%)

TECHNICAL DATA

LUMINAIRE

Code	267133	267143
Power (LED)	14W	14W
Beam	10°	35°
Delivered lms	1049	1049

APPROVALS



ONE4TWO CL™ - CEILING & CANOPY EXTERIOR

DIMENSIONAL DIAGRAMS

