

# ONE4TWO™ - SMALL - WALL

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# ONE4TWO™ - SMALL - WALL



# ONE4TWO™ - SMALL - WALL

**ONE4TWO** is a facade light designed with a robust cylindrical aesthetic and engineered with exceptional power in both light output and optical control. Available with two lumen packages with either narrow or medium beams. An internal reflector ensures efficient light distribution allowing the cylinder to be mounted at higher elevations for wayfinding or to accent facade features.

## GENERAL SPECIFICATION

### Housing

Die-cast and extruded aluminium.

### External Screws

Stainless steel.

### Lens

Clear glass.

### Gaskets

One piece silicone.

### Reflector

High purity aluminium, silver anodised.

### Finish

Silver powder coated light gray or black coated as standard.

### Drivers

HPF, electronic for 120-277V (EU-240V).

### Minimum Starting Temperature

-20°C.

### Weight

Maximum 8.8lb.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Dark Sky Friendly

Dark Sky Friendly if ordered with 3000K CCT and direct only.

## MOUNTING & OPTICS



Ext-Wall Downlight



Ext-Wall Up/Down



10°



35°



Dark Sky Friendly

# ONE4TWO™ - SMALL - WALL

## HOW TO ORDER

### A. LUMINAIRE

**266033** 10° up + 35° down, 932lm  
**266123** 35° down, 466lm

**266013** 10° up + 10° down, 932lm

**266023** 35° up + 35° down, 932lm

**266113** 10° down, 466lm

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**F2** Black Metallic Textured

**GR** Light Gray

### D. DIMMING

**DB** 0-10V Dimming (10%)<sup>1</sup>

<sup>1</sup> Dimming is equal to or less than 10%.

## TECHNICAL DATA

### LUMINAIRE

| Code          | <b>266033</b>     | <b>266013</b>     | <b>266023</b>     | <b>266113</b> | <b>266123</b> |
|---------------|-------------------|-------------------|-------------------|---------------|---------------|
| Power (LED)   | 2 x 6W            | 2 x 6W            | 2 x 6W            | 6W            | 6W            |
| Delivered lms | 932lm             | 932lm             | 932lm             | 466lm         | 466lm         |
| Distribution  | 10° up + 35° down | 10° up + 10° down | 35° up + 35° down | 10° down      | 35° down      |

### FINISH



Black Metallic Textured



Light Gray

### APPROVALS



# ONE4TWO™ - SMALL - WALL

## DIMENSIONAL DIAGRAMS

