

# 0000H™ - CONTINUOUS WALL

Project Name:




Fixture Type:

Fixture Code:

Quantities:



0000H™ - CONTINUOUS WALL



# 0000H™ - CONTINUOUS WALL

**0000H** dazzles up traditional linear lighting concepts with an innovative louver system. An array of ellipses is incurved to conform to a tunnel-shaped profile creating a subtle aesthetic and sublime lighting effect. The louver system not only tempers the starkness of the commonly exposed diffuser and adds an enchanting decorative feature, but also offers visual comfort by minimizing glare. The injection-molded louvers come in 5 finishes: Black for the highest glare control, White for higher reflectance and performance, and for an interior design enhancement, satinized finishes Satin Chrome, Satin Gold, and Satin Champagne. Ooohh presents a simple way to transform a functional light into a luxurious design feature.

## GENERAL SPECIFICATION

### Body

Aluminum.

### Diffuser

Opal acrylic.

### PoE

Can be integrated into your data network via Power over Ethernet (PoE) connectivity.

### Drivers

HPF electronic drivers for 120-277V, 347V (EU-240V). The driver is integral to the fixture housing.

### Integral Emergency system

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

### Reported L70 @25°C (77°F)

> 60,000 hrs @ 2000 lumens/ft (6000 lumens/m)

### Tunable White

Tunable white available, consult factory.

### Designed by

Serge Cornelissen.

### Finish

Powder coated.

### Mechanical

Luminaires mount directly over J box (by others).

### BIOS

For circadian lighting, consult factory.

### Delivered lumens

Delivered lumens & LPW based on 4000K CRI 80+

### Sensors

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.

### Estimated L70 @25°C (77°F)

> 165,000 hrs @ 2000 lumens/ft (6000 lumens/m)

### Approvals

Damp Rated.


### Design

US Pat. No. D969,395.


## MOUNTING & OPTICS



Wall - up/down




Direct DD1



Direct DD4




Indirect UD2



Indirect UD3



Bios



Declare



PoE



# 0000H™ - CONTINUOUS WALL

## HOW TO ORDER

### A. LUMINAIRE

**HLNW1W** Direct

**HLNW2W** Direct/Indirect

One power cord for every 50 linear feet.

### B. LENGTH OF RUN

**SFA** \_ \_ \_ \_

The minimum length of order is 4ft. Lengths are to be in 2ft increments.

Example: 4ft = SFA0400

Example: 10ft = SFA1000

Example: 50ft = SFA5000

For runs over 50ft in length, consult factory.

### C. MAX LENGTH PER SECTION

**SL04** 4ft

**SL06** 6ft

**SL08** 8ft

**SL10** 10ft

**SL12** 12ft

You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4 10ft segments. For special requirements, please contact sales@betacalco.com.

### D. LOUVER

**LV2** Black

**LV3** White

**LV4** Satin Chrome

**LV6** Satin Gold <sup>1</sup>

**LV9** Satin Champagne <sup>1</sup>

<sup>1</sup> There will be a slight color cast on the wall when using the Satin Gold or Satin Champagne louvers.

### E. LM/FT (DIRECT)

**LPF020** 200 lm/ft

**LPF030** 300 lm/ft

**LPF040** 400 lm/ft

**LPF050** 500 lm/ft

**LPF060** 600 lm/ft

**LPF070** 700 lm/ft

**LPF080** 800 lm/ft

**LPF100** 1000 lm/ft

**LPF120** 1200 lm/ft

**LPF130** 1300 lm/ft

Lumens/ft are determined by the color of the Louver. Consult website for available lumens/ft based on selected louver.

### F. LM/FT (INDIRECT)

**LPG000** Not required

**LPG020** 200 lm/ft

**LPG040** 400 lm/ft

**LPG060** 600 lm/ft

**LPG080** 800 lm/ft

**LPG100** 1000 lm/ft

**LPG120** 1200 lm/ft

**LPG140** 1400 lm/ft

**LPG165** 1650 lm/ft

Consult website for available lumens/ft based on selected louver.

### G. CRI

**CR80** CRI 80+

**CR90** CRI 90+

### H. CCT DIRECT

**CTA30** 3000K

**CTA35** 3500K

**CTA40** 4000K

### I. CCT INDIRECT

**CTB00** Not required

**CTB30** 3000K

**CTB35** 3500K

**CTB40** 4000K



# 0000H™ - CONTINUOUS WALL

## J. DIRECT DIFFUSER

**DD1** Asymmetric diffuser

**DD4** Comfort Diffuser

## K. UPLIGHT DIFFUSER

**UD0** Not required

**UD2** Opal diffuser

**UD3** Asymmetric diffuser <sup>1</sup>

<sup>1</sup> Available up to 1200 lm/ft. The asymmetric distribution will be directed away from the wall.

## L. UPLIGHT BLACKOUT PLATE

**UB00** Not required

**UB\_ \_** Blackout plate <sup>1</sup>

<sup>1</sup> Available on a per foot basis. May be required to prevent lighting up duct work in a loft type application.

## M. VOLTAGE

**V1** 120/277V

**V2** 240V <sup>1</sup>

**V3** 347V <sup>2</sup>

**V4** Low Voltage <sup>3</sup>

<sup>1</sup> Not available in North America.

<sup>2</sup> Only available with DA01 dimming.

<sup>3</sup> Only available with DA45 dimming.

## N. DIMMING

**DA01** 0-10V Dimming 1.0%

**DA02** 0-10V Dimming 0.1% <sup>1</sup>

**DA20** DALI Dimming 0.1% <sup>1</sup>

**DA21** DALI Dimming 1.0% <sup>1</sup>

**DA30** DSI/switchDim <sup>2</sup>

**DA45** PoE <sup>3</sup>

<sup>1</sup> Not available with V3.

<sup>2</sup> Not available in North America.

<sup>3</sup> Only available with V4.

## O. FIXTURE FINISH

**FA01** White

**FA02** Black Metallic - Textured

**FA20** Silver Metallic - Textured

**FA25** Gold Metallic - Textured

**FA27** Wood grain - Light Cherry <sup>1</sup>

**FA28** Wood grain - Dark Walnut <sup>1</sup>

**FA44** Midnight Blue Metallic - Textured

**FA45** Copper Metallic

**FA46** Charcoal Metallic - Textured

**FA47** Bronze Metallic - Textured

**FA52** Champagne Metallic

**FA53** Red Metallic - Textured

<sup>1</sup> Longer than normal lead times may apply, consult factory.

## P. EMERGENCY

**E0** Not required

**E1** Emergency system - Integral

**E3** Emergency generator circuit <sup>1</sup>

<sup>1</sup> A drawing will be required at time of ordering to determine the required number and location of the emergency sections or generator circuits. Not available in 347V.

## Q. CIRCUITS

**CS1** Single circuit

**CS2** Dual circuit <sup>1</sup>

## R. SENSORS

# 0000H™ - CONTINUOUS WALL


## TECHNICAL DATA

### LUMINAIRE

One power cord for every 50 linear feet.


Code	HLNW1W	HLNW2W
Light Direction		

### LOUVER



<sup>1</sup> There will be a slight color cast on the wall when using the Satin Gold or Satin Champagne louvers.

### FINISH



<sup>1</sup> Longer than normal lead times may apply, consult factory.


### APPROVALS



# 0000H™ - CONTINUOUS WALL

## PERFORMANCE DATA

### DIRECT COMFORT (DD4) - WHITE LOUVER




LUMEN/FT
1300
1200
1000
800
700
600
500
400
300
200

WATT/FT
13
11
9
7
6
5
4
3
3
2

LPW
106
108
110
114
115
117
119
121
126
128

### DIRECT COMFORT (DD4) - BLACK LOUVER




LUMEN/FT
700
600
500
400
300
200

WATT/FT
13
11
9
7
5
3

LPW
57
58
59
61
63
65

### DIRECT COMFORT (DD4) - SATIN CHROME LOUVER



LUMEN/FT
1000
800
700
600
500
400
300
200

WATT/FT
13
9
9
7
5
4
3
2

LPW
84
87
89
90
93
95
95
98


# 0000H™ - CONTINUOUS WALL

## DIRECT COMFORT (DD4) - SATIN GOLD LOUVER

### LUMEN/FT

### WATT/FT

### LPW



1000
800
700
600
500
400
300
200

13
9
9
7
5
4
3
2


82
85
87
88
91
93
93
96

## DIRECT COMFORT (DD4) - SATIN CHAMPAIGN LOUVER

### LUMEN/FT

### WATT/FT

### LPW



1000
800
700
600
500
400
300
200

13
9
9
7
5
4
3
2


84
87
89
90
93
95
95
98

## INDIRECT BATWING (UD1)

### LUMEN/FT

### WATT/FT

### LPW



1600
1400
1200
1000
800
600
400
200

13
10
9
7
6
4
3
1

133
138
142
245
247
151
154
154




# 0000H™ - CONTINUOUS WALL

## INDIRECT ASYMMETRIC (UD3)

### LUMEN/FT

### WATT/FT

### LPW



1200  
1000  
800  
600  
400  
200





13  
10  
9  
6  
4  
2

97  
100  
102  
107  
107  
109  
112


# 0000H™ - CONTINUOUS WALL

## DIMENSIONAL DIAGRAMS

### Isometric Views



Top View [Uplight]




Bottom View [Downlight]


# 0000H™ - CONTINUOUS WALL

## Wall Mount Configurations


### 4FT




### 6FT



### 8FT



### 10FT



### 12FT

