

# PEYOTE™ - BOLLARDS

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# PEYOTE™ - BOLLARDS

## GENERAL SPECIFICATION

### Housing

Die-cast and extruded aluminum.

### External Screws

Stainless steel.

### Lens

Clear polycarbonate.

### Gaskets

One piece silicone.

### Finish

Silver powder coated RAL9006 or black powder coated.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V dimming.

### Cable entry

M20 cable gland.

### Mounting

Anchorage rods required for concrete.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Ext-Bollards

# PEYOTE™ - BOLLARDS

## HOW TO ORDER

### A. LUMINAIRE

**8309100** 360° , 933 lms

**8309110** 180° , 466 lms

**8309120** 2 x 90° , 466 lms

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**GR** Light Gray RAL 9006

### D. OPTIONS

**8309199** Anchorage base for poured concrete

## TECHNICAL DATA

### LUMINAIRE

Code	<b>8309100</b>	<b>8309110</b>	<b>8309120</b>
Power (LED)	14W	14W	14W
Delivered lms	933	466	466
LPW	67	33	33
Distribution	360°	180°	2 x 90°

## APPROVALS



# PEYOTE™ - BOLLARDS

## DIMENSIONAL DIAGRAMS

