

PEYOTE™ - BOLLARDS

Project Name:

Fixture Type:

Fixture Code:

Quantities:



PEYOTE™ - BOLLARDS

GENERAL SPECIFICATION

Housing

Die-cast and extruded aluminum.

External Screws

Stainless steel.

Lens

Clear polycarbonate.

Gaskets

One piece silicone.

Finish

Silver powder coated RAL9006 or black powder coated.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V dimming.

Cable entry

M20 cable gland.

Mounting

Anchorage rods required for concrete.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Ext-Bollards

PEYOTE™ - BOLLARDS

HOW TO ORDER

A. LUMINAIRE

8309100 360° , 933 lms

8309110 180° , 466 lms

8309120 2 x 90° , 466 lms

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

GR Light Gray RAL 9006

D. OPTIONS

8309199 Anchorage base for poured concrete

TECHNICAL DATA

LUMINAIRE

Code	8309100	8309110	8309120
Power (LED)	14W	14W	14W
Delivered lms	933	466	466
LPW	67	33	33
Distribution	360°	180°	2 x 90°

APPROVALS



PEYOTE™ - BOLLARDS

DIMENSIONAL DIAGRAMS

