

PEYOTE™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



PEYOTE™ - WALL SURFACE EXTERIOR

GENERAL SPECIFICATION

Housing Die-cast and extruded aluminium.	External Screws Stainless steel.
Lens Clear glass.	Gaskets One piece silicone.
Finish Silver powder coated light gray or black coated as standard. <i>(For custom finishes please contact factory).</i>	Drivers HPF, electronic for 120-277V (EU-240V).
Minimum Starting Temperature -30°C.	Weight Maximum 8.8lb.
Delivered Lumens Delivered lumens & LPW based on 3000K (min 80 CRI).	

OPTICS & FEATURES



Ext-Wall Downlight Ext-Wall Up/Down

PEYOTE™ - WALL SURFACE EXTERIOR

HOW TO ORDER

A. LUMINAIRE

8309000 360°, 933 lms

8309010 180°, 466 lms

8309020 2 x 90°, 466 lms

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

GR Light Gray

D. OPTIONS

8309099 Anchorage Base for poured concrete

TECHNICAL DATA

LUMINAIRE

Code	8309000	8309010	8309020
Power (LED)	14W	14W	14W
Delivered lms	933	466	466
LPW	67	33	33
Distribution	360°	180°	2 x 90°





APPROVALS



PEYOTE™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

143mm/5.6" DIA



160mm/6.3" DIA