
Project Name: Fixture Type:

Fixture Code: Quantities:











Buoyant and cheerful, PUZZLE is a collection of curvilinear pendants consisting of 5 organic shapes each with 3 sizes. What these shapes are is an enigma left open to the individual's imagination and designed for creating remarkable configurations that complement a variety of design themes.

GENERAL SPECIFICATION

Body

Aluminum.

Suspension

Steel cables.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15'/4.5m. Test switch fits a single gang box (not supplied).

Drivers

HPF electronic drivers for 120-277V, 37V (EU-240V). Drivers are either remote mounted or integral to the canopy depending on the size of the fixture.

Mechanical

Luminaires mount directly over J box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

Approvals

Damp Rated.

Seismic Bracing

Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

OPTICS & FEATURES











Direct-indirect

Finish

Powder coated.

Power cable

Silver braided.

Remote Mounting Of Drivers

Wire Size 18 AWG - Max distance (from fixture to drivers) 40' (12.2m), Wire size 16 AWG - Max distance 60' (18.3m), Wire size 14 AWG - Max distance 90 (27.4m). Drivers must be accessible after installation.

Diffuser

Protruding Lens (0.9"/2.1mm).

Sensors

Consult factory regarding sensor compatibility.

Reported L70 @25°C (77°F)

> 50,000 hrs.

Patent No.

D827909, D827187, D827908, D828611, D827907.



HOW TO ORDER

A. CHOOSE SHAPE AND SIZE

Select from one of the following 5 shapes. Three sizes per Shape, consult dimensional diagrams for actual sizes.

SHAPE "A"



PULP1P01 A1, Direct, 3200 lms **PULP2P02** A2 Direct/Indirect, 10300 lms

PULP1P02 A2, Direct, 5100 lms **PULP2P03** A3 Direct/Indirect, 14100 lms

PULP1P03 A3, Direct, 7000 lms

PULP2P01 A1, Direct/Indirect, 6700 lms

SHAPE "B"



PULP1P04 B1 Direct, 3000 lms **PULP2P05** B2, Direct/Indirect, 9500 lms

PULP1P05 B2 Direct, 4800 lms **PULP2P06** B3 Direct/Indirect, 13400 lms

PULP1P06 B3 Direct, 6600 lms

PULP2P04 B1, Direct/Indirect, 5700 lms

SHAPE "C"



PULP1P07 C1 Direct, 3000 lms **PULP2P08** C2 Direct/Indirect, 9500 lms

PULP1P08 C2 Direct, 4800 lms **PULP2P09** C3 Direct/Indirect, 13400 lms

PULP1P09 C3 Direct, 6600 lms

PULP2P07 C1 Direct/Indirect, 6300 lms

SHAPE "D"



PULP1P10 D1 Direct, 3200 lms **PULP2P11** D2 Direct/Indirect, 10300 lms

PULP1P11 D2 Direct, 5000 lms **PULP2P12** D3 Direct/Indirect, 14100 lms

PULP1P12 D3 Direct, 7000 lms

PULP2P10 D1 Direct/Indirect, 6700 lms

SHAPE "E"



PULP1P13 E1 Direct, 3000 lms
PULP2P14 E2 Direct/Indirect, 10300 lms

PULP1P14 E2 Direct, 5000 lms **PULP2P15** E3 Direct/Indirect, 14100 lms

PULP1P15 E3 Direct, 7000 lms

PULP2P13 E1, Direct/Indirect, 6300 lms

B. LUMENS (DIRECT) LPF017 175 lm/ft ¹ **LPF026** 265 lm/ft ² LPF035 350 lm/ft 3 ¹ Based of 50% of total output. ² Based on 75% of total output. $^{\scriptsize 3}$ 100% of total output. C. LUMEN (INDIRECT) **LPG017** 175 lm/ft ¹ **LPG026** 265 lm/ft ² **LPG035** 350 lm/ft ³ LPG000 Not required ¹ Based of 50% of total output. ² Based on 75% of total output. ³ 100% of total output. D. CRI CR80 CRI 80+ CR90 CRI 90+ E. CCT (DIRECT) **CTA27** 2700K **CTA30** 3000K **CTA35** 3500K **CTA40** 4000K F. CCT (INDIRECT) CTB00 Not required **CTB27** 2700K **CTB30** 3000K **CTB35** 3500K **CTB40** 4000K **G. VOLTAGE** V1 120/277V V2 240V 1 **V3** 347V ² ¹ Not available in North America. ² Available with DA01 only. H. DIMMING **DA01** 0-10V Dimming 1.0% **DA02** 0-10V Dimming 0.1% ¹ DA20 DALI Dimming 0.1% 1 DA21 DALI Dimming 1.0% 1 ¹ Remote, not available with V3. I. SUSPENSION **SS1** Vertical, Remote driver **SS3** Vertical, Driver Integral to Canopy ¹ ¹ Available with DA01 only. J. FINISH FA01 White FA02 Black Metallic - Textured FA20 Silver Metallic - Textured FA25 Gold Metallic - Textured

K. CANOPY FINISH

FA52 Champagne Metallic

FA44 Midnight Blue Metallic - Textured

CF01 White CF02 Black Metallic - Textured CF20 Silver Metallic - Textured CF25 Gold Metallic - Textured CF46 Charcoal Metallic - Textured CF47 Bronze Metallic - Textured **CF44** Midnight Blue Metallic - Textured CF45 Copper Metallic CF52 Champagne Metallic CF53 Red Metallic - Textured

FA46 Charcoal Metallic - Textured



FA45 Copper Metallic

FA53 Red Metallic - Textured

FA47 Bronze Metallic - Textured

L. EMERGENCY

E0 Not required **E2** Emergency system - Remote

M. CIRCUITS

CS1 Single circuit **CS2** Dual circuit

TECHNICAL DATA

SHAPE "A"



Code	PULP1P01	PULP1P02	PULP1P03	PULP2P01	PULP2P02	PULP2P03	
Size	A1	A2	А3	A1	A2	А3	
Light Direction	Direct	Direct	Direct	Direct/Indirect	Direct/Indirect	Direct/Indirect	
Wattage	39W	61W	84W	80	123	168	
Delivered Ims	3200	5100	7000	6700	10300	14100	
LPW	83	83	83	84	84	84	
Suspension Points	3	3	4	3	3	4	

SHAPE "B"



Code	PULP1P04	PULP1P05	PULP1P06	PULP2P04	PULP2P05	PULP2P06
Size	B1	B2	B3	B1	B2	B3
Light Direction	Direct	Direct	Direct	Direct/Indirect	Direct/indirect	Direct/Indirect
Wattage	36	58	80	68	113	160
Delivered Ims	3000	4800	6600	5700	9500	13400
LPW	83	83	83	84	84	84
Suspension Points	3	4	5	3	4	5

SHAPE "C"



Code	PULP1P07	PULP1P08	PULP1P09	PULP2P07	PULP2P08	PULP2P09
Size	C1	C2	C3	C1	C2	C3
Light Direction	Direct	Direct	Direct	Direct/Indirect	Direct/Indirect	Direct/Indirect
Wattage	36	58	80	75	113	160
Delivered Ims	3000	4800	6600	6300	9500	13400
LPW	83	83	83	84	84	84
Suspension Points	3	4	5	3	4	5

SHAPE "D"



Code PULP1P10	PULP1P11	PULP1P12	PULP2P10	PULP2P11	PULP2P12
Size D1	D2	D3	D1	D2	D3
Light Direction Direct	Direct	Direct	Direct/Indirect	Direct/indirect	Direct/indirect
Wattage 39	61	84	80	123	168
Delivered Ims 3200	5000	7000	6700	10300	14100
LPW 83	83	83	84	84	84
Suspension Points 3	4	5	3	4	5

SHAPE "E"



Code	PULP1P13	PULP1P14	PULP1P15	PULP2P13	PULP2P14	PULP2P15
Size	E1	E2	E3	E1	E2	E3
Light Direction	Direct	Direct	Direct	Direct/Indirect	Direct/indirect	Direct/Indirect
Wattage	36	61	84	75	123	168
Delivered Ims	3000	5000	7000	6300	10300	14100
LPW	83	83	83	84	84	84
Suspension Points	3	4	5	3	4	5

FIXTURE FINISH



White

Champagne Metallic



Silver Metallic -

Textured



Textured



Textured



Copper Metallic



Textured



Bronze Metallic -

Textured





Black Metallic -

Textured

Red Metallic -Textured

CANOPY FINISH



APPROVALS


Champagne Metallic




Red Metallic -Textured

DIMENSIONAL DIAGRAMS


A1, A2, A3




B1, B2, B3




C1, C2, C3




D1, D2, D3



E1, E2, E3



S1 - Remote Driver



S1 Remote Driver

S3 - Integral Driver

