

# QED™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# QED™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Lens

Laminated glass or opal acrylic with a sandblasted finish.

### Emergency systems

#### Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

#### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Finish

Frame and horizontal reflector plate, white powder coated. Structural cross bars and finials, polished chrome plated.

### Drivers

HPF electronic drivers, 120/277V (EU-240V). 0-10V, 1% dimming standard.

### Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

### Mechanical

Luminaires mount directly over a junction box (not supplied).

## OPTICS & FEATURES



Suspended 2 sides

# QED™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**441850** 44 1850

**441852** 44 1852

**442450** 44 2450

**442452** 44 2452

**443650** 44 3650

**443652** 44 3652

**443620** 44 3620

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. SUSPENSION

**TS** Tube suspension

**CS** Cable suspension

### D. DIFFUSERS

**OA** Opal acrylic

**OG** Opal glass

### E. DIMMING

**DA** DALI dimming (0-1%)

### F. EMERGENCY SYSTEM

**EM** Emergency System (not available with DALI)

**RE** Remote Emergency

### G. OPTIONS

**OT** Other Painted Finish (for horizontal reflector panel only, RAL number required)

# QED™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>441850</b>	<b>441852</b>	<b>442450</b>	<b>442452</b>	<b>443650</b>	<b>443652</b>
<b>Power (LED)</b>	28W	28W down/28W up	56W	56W down/29W up	56W	56W down/29W up
<b>Delivered lms</b>	1856	5177	3961	7277	4166	7463
<b>LPW</b>	66	92	70	86	74	88
<b>Width (B)</b>	24"	24"	30"	30"	36"	36"
<b>Width (A)</b>	8"	8"	10.25"	10.25"	12"	12"
<b>Height (A)</b>	21"	21"	26"	26"	31"	31"
<b>Height (B)</b>	12"	12"	24"	24"	24"	24"
<b>Code</b>	<b>443620</b>					
<b>Power (LED)</b>	56W down/36W up					
<b>Delivered lms</b>	8298					
<b>LPW</b>	91					
<b>Width (B)</b>	36"					
<b>Width (A)</b>	12"					
<b>Height (A)</b>	31"					
<b>Height (B)</b>	24"					

### APPROVALS



IP20



# QED™ - SUSPENDED

## DIMENSIONAL DIAGRAMS

