Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Lens

Laminated glass or opal acrylic with a sandblasted finish.

Emergency systems

Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15′. Test switch fits a single gang box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended 2 sides

Finish

Frame and horizontal reflector plate, white powder coated. Structural cross bars and finials, polished chrome plated.

Drivers

HPF electronic drivers, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

Mechanical

Luminaires mount directly over a junction box (not supplied).

HOW TO ORDER

A. LUMINAIRE

441850 441850 **441852** 441852 **441852 442450** 442450 **442450 442452** 442452

443650 44 3650 **443652** 443652 **443620** 443620

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. SUSPENSION

TS Tube suspension **CS** Cable suspension

D. DIFFUSERS

OA Opal acrylic **OG** Opal glass

E. DIMMING

DA DALI dimming (0-1%)

F. EMERGENCY SYSTEM

EM Emergency System (not available **RE** Remote Emergency

with DALI)

G. OPTIONS

OT Other Painted Finish (for horizontal reflector panel only, RAL number required)

TECHNICAL DATA

LUMINAIRE

Code	441850	441852	442450	442452	443650	443652
Power (LED)	28W	28W down/28W up	56W	56W down/29W up	56W	56W down/29W up
Delivered Ims	1856	5177	3961	7277	4166	7463
LPW	66	92	70	86	74	88
Width (B)	24"	24"	30"	30"	36"	36"
Width (A)	8"	8"	10.25"	10.25"	12"	12"
Height (A)	21"	21"	26"	26"	31"	31"
Height (B)	12"	12"	24"	24"	24"	24"

443620 Code

Power (LED) 56W down/36W up

Delivered Ims 8298 LPW 91 Width (B) 36" Width (A) 12" Height (A) 31" Height (B) 24"

APPROVALS











DIMENSIONAL DIAGRAMS

