

QED™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 5

QED™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Frame and horizontal reflector plate, white powder coated. Structural cross bars and finials, polished chrome plated.

Lens

Laminated glass or opal acrylic with a sandblasted finish.

Drivers

HPF electronic drivers, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Emergency systems

Integral

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.

Remote

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).


Mechanical

Luminaires mount directly over a junction box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended 2 sides



QED™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

441850 441850

443650 44 3650

441852 441852

443652 443652

442450 442450

443620 443620

442452 442452

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. SUSPENSION

TS Tube suspension

CS Cable suspension

D. DIFFUSERS

OA Opal acrylic

OG Opal glass

E. DIMMING

DA DALI dimming (0-1%)

F. EMERGENCY SYSTEM

EM Emergency System (not available with DALI)

RE Remote Emergency

G. OPTIONS

OT Other Painted Finish (for horizontal reflector panel only, RAL number required)



QED™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	441850	441852	442450	442452	443650	443652
Power (LED)	28W	28W down/28W up	56W	56W down/29W up	56W	56W down/29W up
Delivered lms	1856	5177	3961	7277	4166	7463
LPW	66	92	70	86	74	88
Width (B)	24"	24"	30"	30"	36"	36"
Width (A)	8"	8"	10.25"	10.25"	12"	12"
Height (A)	21"	21"	26"	26"	31"	31"
Height (B)	12"	12"	24"	24"	24"	24"
Code	443620					
Power (LED)	56W down/36W up					
Delivered lms	8298					
LPW	91					
Width (B)	36"					
Width (A)	12"					
Height (A)	31"					
Height (B)	24"					

APPROVALS



QED™ - SUSPENDED

DIMENSIONAL DIAGRAMS

