


# RING BLADE™ SHORT SPECIFICATION SHEET



Fixture Type	Fixture Code	Quantities



## 1 HOW TO ORDER

### 1. LUMINAIRE TYPE

**RBDP** Pendant **RBDC** Ceiling

2. DIAMETER

**SL03** 3ft, 9700 lms **SL04** 4ft, 13000 lms **SL05** 5ft, 16400 lms **SL06** 6ft, 19700 lms

3. DISTRIBUTION

DR1 Direct 100% DR2 Direct 54% / Indirect 46%

4. LM/FT

LPF040 400 lm/ft <sup>1</sup> LPF060 600 lm/ft <sup>123</sup> LPF080 800 lm/ft <sup>124</sup> LPF100 1000 lm/ft <sup>25</sup>

### 5. CRI

CR90 CRI 90+

## 6. CCT

CTA27 2700K CTA30 3000K CTA35 3500K CTA40 4000K

## 7. VOLTAGE

**V1** 120/277V **V2** 240V <sup>1</sup> **V3** 347V <sup>2</sup> **V4** Low Voltage <sup>3</sup>

<sup>&</sup>lt;sup>1</sup> Available with DR1 (Direct only)

<sup>&</sup>lt;sup>2</sup> Available with DR2 (Direct/Indirect)

<sup>&</sup>lt;sup>3</sup> Based on 60% of total output (for DR2)

<sup>&</sup>quot;Based on 80% of total output (for DR2)

<sup>&</sup>lt;sup>5</sup> 100% of total output (for DR2)

<sup>&</sup>lt;sup>1</sup> V2 not available in North America.

<sup>&</sup>lt;sup>2</sup> V3 available with DA01 dimming only.

<sup>&</sup>lt;sup>3</sup> V4 available with DA45 dimming only.



### 8. DIMMING (REMOTE)

**DA01** 0-10V Dimming 1.0% **DA02** 0-10V Dimming 0.1% <sup>1</sup> **DA20** DALI Dimming 0.1% <sup>1</sup> **DA21** DALI Dimming 1.0% <sup>1</sup>

DA30 DSI/switchDim 12 DA45 PoE 3

#### 9. SUSPENSION

SSO Not required SS6 POS, Vertical, Remote driver SS7 POS, Hub, Remote driver SS9 POS, Hub, Driver Integral to Canopy 12

#### **10. FIXTURE FINISH**

FA01 White FA02 Black Metallic - Textured FA20 Silver Metallic - Textured FA25 Gold Metallic - Textured FA44 Midnight Blue Metallic - FA45 Copper Metallic FA46 Charcoal Metallic - FA47 Bronze Metallic - Textured

Textured Textured

FA52 Champagne Metallic FA53 Red Metallic - Textured

#### 11. CANOPY FINISH

CF00 Not required CF01 White CF02 Black Metallic - Textured CF20 Silver Metallic - Textured

CF25 Gold Metallic - Textured CF44 Midnight Blue Metallic - CF45 Copper Metallic - CF46 Charcoal Metallic -

Textured Textured

CF47 Bronze Metallic - Textured CF52 Champagne Metallic CF53 Red Metallic - Textured

#### 12. ACOUSTIC PANEL COLOR

AP00 Not requiredAP02 CitrusAP04 WhiteAP08 Red CoffeeAP11 Light GrayAP13 Apple GreenAP22 BlueAP26 Sesame GrayAP27 BlackAP47 Navy PeonyAP60 Pure RedAP73 Cloudburst

AP89 Douglas Fir APW01 Oak

Acoustic panels 48" and larger will include a visible seam.

For accompanying non-illuminating acoustic panels, see our Acoustic Circles, Quads, Triangles, and Ellipse spec pages.

Other finishes available. Contact factory.

<sup>&</sup>lt;sup>1</sup> Not available with V3 or V4.

<sup>&</sup>lt;sup>2</sup> DA30 not available in North America

<sup>&</sup>lt;sup>3</sup> DA45 used V4 only.

Available with V1 (120V) only. The minimum suspension height relative to diameter is as follows: 3ft = 18", 4ft = 24", 5ft = 30", 6ft = 36".

<sup>&</sup>lt;sup>2</sup> Available with V1 (120V) only.



## 13. EMERGENCY

**EO** Not required

**E2** Emergency system - Remote <sup>1</sup>

<sup>&</sup>lt;sup>1</sup> Not available in Integral or with 347V. Consult factory.