

RING BLADE™

Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE TYPE

RBDP Pendant

RBDC Ceiling

B. DIAMETER

SL03 3ft, 9000 lms

SL04 4ft, 12000 lms

SL05 5ft, 16400 lms

SL06 6ft, 19400 lms

C. DISTRIBUTION

DR1 Direct 100%

DR2 Direct 50% / Indirect 50%

D. LM/FT

LPF040 400 lm/ft¹

LPF060 600 lm/ft^{1 2}

LPF080 800 lm/ft^{1 2}

LPF100 1000 lm/ft²

¹ 100% Direct light

² 54 Direct light/46% Indirect light

E. CRI

CR90 CRI 90+

F. CCT

CTA27 2700K¹

CTA30 3000K

CTA35 3500K

CTA40 4000K

¹ Longer than normal lead times may apply, consult factory.

G. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V²

V4 Low Voltage³

¹ V2 not available in North America.

² V3 available with DA01 dimming only.

³ V4 available with DA45 dimming only.

H. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1%¹

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

DA30 DSI/switchDim^{1 2}

DA45 PoE³

¹ Not available with V3 or V4.

² DA30 not available in North America

³ DA45 used V4 only.

I. SUSPENSION

SS0 Not required

SS6 POS, Vertical, Remote driver

SS7 POS, Hub, Remote driver¹

SS9 POS, Hub, Driver Integral to Canopy^{1 2}

¹ Available with V1 (120V) only. The minimum suspension height relative to diameter is as follows: 3ft = 18", 4ft = 24", 5ft = 30", 6ft = 36".

² Available with V1 (120V) only.



RING BLADE™

J. FIXTURE FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured
FA52 Champagne Metallic	FA53 Red Metallic - Textured		

K. CANOPY FINISH

CF00 Not required	CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured
CF25 Gold Metallic - Textured	CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured
CF47 Bronze Metallic - Textured	CF52 Champagne Metallic	CF53 Red Metallic - Textured	

L. ACOUSTIC PANEL COLOR

AP00 Not required	AP04 White	AP13 Apple Green	AP22 Blue
AP11 Light Gray	AP26 Sesame Gray	AP27 Black	

Available up to 5ft diameter. Larger sizes available with visible seams, consult factory.
For accompanying non-illuminating acoustic panels see our Acoustic Circles, Quads, Triangles and Ellipse spec pages.
Other finishes available. Consult factory.

M. EMERGENCY

E0 Not required	E2 Emergency system - Remote ¹
------------------------	--

¹ Not available in Integral or with 347V. Consult factory.



RING BLADE™

DIMENSIONAL DIAGRAMS

DISTANCE TO CEILING SURFACE MOUNT




CROSS SECTION




Diameter	Minimum Suspension Height
3ft [914mm]	15" [381mm]
4ft [1219mm]	20" [508mm]
5ft [1524mm]	25" [635mm]
6ft [1828mm]	35" [889mm]
7ft [2133mm]	40" [1016mm]


Distance to ceiling
Hub Mount




Distance to ceiling
Vertical Mount



Hub Remote POS (SS7)



Hub Integral POS (SS9)



Vertical Remote POS (SS6)

