

RING™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

RNGF1P02 2ft, 6000 lms
RNGF1P06 6ft, 21000 lms

RNGF1P03 3ft, 10000 lms
RNGF1P07 7ft, 26000 lms

RNGF1P04 4ft, 14000 lms

RNGF1P05 5ft, 18000 lms

Note: Recommended for installation on a hard ceiling.

B. LM/FT

LPF055 550 lm/ft¹

LPF082 825 lm/ft²

LPF110 1100 lm/ft³

¹ Based on 50% of total output.

² Based on 75% of total output.

³ 100% of total output.

C. CRI

CR80 CRI 80+

D. CCT

CTA27 2700K
CTA50 RGBW

CTA30 3000K

CTA35 3500K

CTA40 4000K

E. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V²

¹ Not available in North America.

² Available with DA01 dimming only. Not available with CTA50

F. DIMMING

DA01 0-10V Dimming 1.0%
DA30 DSI/switchDim^{1 2}

DA02 0-10V Dimming 0.1%¹
DA40 DMX Dimming¹

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

¹ Not available with V3.

² Not available in North America.

G. FINISH

FA01 White
FA27 Wood grain - Light Cherry¹
FA46 Charcoal Metallic - Textured

FA02 Black Metallic - Textured
FA28 Wood grain - Dark Walnut¹
FA47 Bronze Metallic - Textured

FA20 Silver Metallic - Textured
FA44 Midnight Blue Metallic - Textured
FA52 Champagne Metallic

FA25 Gold Metallic - Textured
FA45 Copper Metallic
FA53 Red Metallic - Textured

¹ Longer than normal lead times may apply, consult factory.

H. EMERGENCY

E0 Not required

E1 Emergency system - Integral¹

¹ Not available with 347V



RING™ - CEILING

DIMENSIONAL DIAGRAMS

