

Project Name:	Fixture Type:
Fixture Code:	Quantities:



The RING DISC represents a refined evolution of luminaire design, offering a streamlined alternative to the classic disc form factor. With its ultra-thin profile and minimalist aesthetic, RING DISC blends seamlessly into the architectural environment, providing soft, even illumination without overwhelming the space design. This fixture's understated elegance allows it to enhance the ambiance subtly, contributing to a cohesive and harmonious atmosphere. Ideal for those seeking a sophisticated lighting solution, RING DISC delivers all the benefits of contemporary lighting technology in a sleek, unobtrusive form, setting a new standard for architectural integration.

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Suspension

P.O.S. Power over suspension cable.

Remote Emergency system

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

Acoustic Panels NRC Rating

0.80

Acoustic Panels Material

100% recycled polyester fiber (PET).

PoE

Ring can integrate into your data network via Power over Ethernet (PoE) connectivity.

Delivered Lumens

Delivered lumens & LPW based on 4000K (min 90 CRI).

Approvals

Damp Location (Indoor use only).

Seismic Bracing

Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.

Finish

Powder coated.

Diffusers

Optical grade clear polymethyl methacrylate.

Drivers

Remote, HPF electronic drivers for 120-277V (EU-240V) dimming. Wire size 18 AWG - max distance (from fixture to drivers) 40' (12.2m), wire size 16 AWG - max distance 60' (18.3m), wire size 14 AWG - max distance 90' (27.4m). Drivers must be accessible after installation. Drivers are either remote mounted or integral to the canopy.

Acoustic Panels Fire Rating

ASTM E84-2018 Class A.

Acoustic Panels Thickness

12mm (0.5")

Mechanical

Luminaires mount directly over J box (by others - North America only).

Reported L70 @25°C (77°F)

> 50,000 hrs.

Design

US Design Patent Pending.

Acoustic Panel Maintenance

Durable and easy to maintain. Dust regularly and clean marks with mild detergent, rinse, and blot.

OPTICS & FEATURES




Suspended Direct



Suspended Direct/Indirect



Direct



Dir-Indirect



Declare



PoE

RING DISC™

HOW TO ORDER

A. LUMINAIRE TYPE

RNDP Pendant

B. ILLUMINATED OR NON-ILLUMINATED

LTD1 Illuminated **LTD2** Non-Illuminated

C. DIAMETER

SL03 3ft, 9700 lms **SL04** 4ft, 13000 lms

D. DISTRIBUTION

DR0 Not required **DR1** Direct 100% **DR2** Direct 48% / Indirect 52%

E. LUMENS

LMA0000 Not required	LMA0170 1700 lms	LMA0230 2300 lms	LMA0300 3000 lms
LMA0340 3400 lms	LMA0460 4600 lms	LMA0520 5200 lms	LMA0610 6100 lms
LMA0690 6900 lms	LMA0900 9000 lms	LMA0920 9200 lms	LMA1205 12050 lms

F. CRI

CR00 Not required **CR90** CRI 90+

G. CCT

CTA00 Not required	CTA27 2700K	CTA30 3000K	CTA35 3500K
CTA40 4000K			

H. VOLTAGE

V0 Not required	V1 120/277V	V2 240V ¹	V3 347V ²
V4 Low Voltage ³			

¹ V2 not available in North America.
² V3 available with DA01 dimming only.
³ V4 available with DA45 dimming only.

I. DIMMING (REMOTE)

DA00 Not required	DA01 0-10V Dimming 1.0%	DA02 0-10V Dimming 0.1% ¹	DA20 DALI Dimming 0.1% ¹
DA21 DALI Dimming 1.0% ¹	DA30 DSI/switchDim ^{1 2}	DA45 PoE ³	

¹ Not available with V3 or V4.
² DA30 not available in North America
³ DA45 used V4 only.

J. SUSPENSION

SS1 Vertical, Aircraft Cable ²	SS2 Hub, Aircraft Cable ²	SS6 POS, Vertical, Remote driver ³	SS7 POS, Hub, Remote driver ^{1 3}
SS9 POS, Hub, Driver Integral to Canopy ^{1 3 4}			

¹ The minimum suspension height relative to diameter is as follows: 3ft = 18", 4ft = 24".
² Available with Pendant - Non Illuminated only.
³ Available with Pendant - Illuminated only.
⁴ Available with V1 (120V) only.

K. FIXTURE FINISH

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured
FA52 Champagne Metallic	FA53 Red Metallic - Textured		

L. CANOPY FINISH

CF00 Not required	CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured
CF25 Gold Metallic - Textured	CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured
CF47 Bronze Metallic - Textured	CF52 Champagne Metallic	CF53 Red Metallic - Textured	

M. ACOUSTIC PANEL COLOR

AP00 Not required	AP02 Citrus	AP04 White	AP08 Red Coffee
AP11 Light Gray	AP13 Apple Green	AP22 Blue	AP26 Sesame Gray
AP27 Black	AP47 Navy Peony	AP60 Pure Red	AP73 Cloudburst
AP89 Douglas Fir	APW01 Oak		

Other finishes available. Contact factory.

N. EMERGENCY

E0 Not required	E2 Emergency system - Remote ¹
------------------------	--


¹ Not available in Integral or with 347V. Consult factory.

TECHNICAL DATA


DIAMETER

Code	SL03	SL04
Diameter	3ft	4ft
Wattage Direct	86	115
Direct lms	6900	9200
LPW Direct	80	80
Down/Up Ratio (Direct)	100/0	100/0
Watts Direct/Indirect	86	115
Direct/Indirect lms	9000	12050
LPW Direct/Indirect	105	105
Down/Up Ration (D/I)	48/52	48/52


FIXTURE FINISH




White




Black Metallic -
Textured




Silver Metallic -
Textured




Gold Metallic -
Textured




Midnight Blue Metallic -
Textured




Copper Metallic




Charcoal Metallic -
Textured



Bronze Metallic -
Textured




Champagne Metallic




Red Metallic -
Textured


CANOPY FINISH




Not required




White




Black Metallic -
Textured




Silver Metallic -
Textured




Gold Metallic -
Textured




Midnight Blue Metallic -
Textured




Copper Metallic




Charcoal Metallic -
Textured



Bronze Metallic -
Textured




Champagne Metallic



Red Metallic -
Textured

ACOUSTIC PANEL FINISH






Other finishes available. Contact factory.


APPROVALS




DIMENSIONAL DIAGRAMS



Hub Remote POS (SS7)



Hub Integral POS (SS9)



Vertical Remote POS (SS6)

