


SCALA™ - RECESSED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



SCALA™ - RECESSED






SCALA™ - RECESSED

SCALA is designed to blend into the architecture while illuminating steps and pathways. With asymmetric light distribution, **SCALA** makes efficient use of the light output directing it to exactly where it is required. There are 4 form factors with various orientations available to suit the exterior aesthetics, as well as 3 polyester-based finishes. This fixture is both Dark Sky (for the 3000K variant) and Turtle friendly, with the amber LED also available. The use of low copper, die-cast aluminum that is highly resistant to oxidation, stainless steel, and silicone makes this a durable fixture that is built to withstand the elements, especially with the IP65 water and dust ingress rating.

GENERAL SPECIFICATION

Housing Low copper, die-cast aluminum highly resistant to oxidation.	Finish Powder coated polyester highly resistant to UV and oxidation.
Lens 3mm/0.12" sodium calcium tempered glass.	Gasket Silicone.
External Screws A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.	Cable Entry Silicone cable gland for cables DIA 10-14mm/0.4-0.55".
Drivers HPF electronic, 120-277V (120V for Type C and D).	Rough-In Housing Thermoplastic.
Mechanical Recessed luminaire for wall mounting only into brick or concrete.	Delivered Lumens Delivered lumens & LPW based on 3000K (min 80 CRI).
Dark Sky Friendly Dark Sky Friendly if ordered with 3000K CCT.	

OPTICS & FEATURES



Ext-Wall Recessed Downlight Assymetrical Dark Sky Friendly

SCALA™ - RECESSED

HOW TO ORDER

A. LUMINAIRE

8208710 A Type, 570 lms	8208712 B Type, 570 lms	8208714 C Type, 285 lms	8208716 C Type, 500 lms
8208718 D Type, 75 lms			

B. CCT

30 3000K (min 80 CRI)	40 4000K (min 80 CRI)	TF Amber LED (Turtle Friendly)
------------------------------	------------------------------	---------------------------------------

C. FINISH

BL Black Metallic Textured	AG Anthracite Gray	GR Light Gray
-----------------------------------	---------------------------	----------------------

D. DIMMING

DB Dimming Types A & B only (0-10V) ¹

¹ Dimming equal to or less than 10%.

E. ROUGH-IN HOUSINGS (REQUIRED)

RIH5408 Rough-In Housing for Type A	RIH5406 Rough-In Housing for Type B	RIH5409 Rough-In Housing for Type C	RIH5410 Rough-In Housing for Type D
--	--	--	--

SCALA™ - RECESSED

TECHNICAL DATA

LUMINAIRE

Code	8208710	8208712	8208714	8208716	8208718
Power (LED)	6W	6W	3W	6W	2W
Type	A	B	C	C	D
Initial Lumens	570	570	285	500	75

LUMINAIRE



FINISH



APPROVALS



SCALA™ - RECESSED

DIMENSIONAL DIAGRAMS

