

SENTI™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 5

SENTI™ - WALL SURFACE EXTERIOR

GENERAL SPECIFICATION

Housing

Die-cast and extruded (low copper) aluminium. Front housing hinges open for access and secures via a bolt hidden behind a spring loaded flap. Central perforated mesh band, optional (PM).

Finish

Exterior grade, metallic powder coated paint.

Gaskets

One piece silicone.

Lens

UV stabilised polycarbonate.

LED arrangement

Single LED to illuminate front diffuser. Single LED for narrow beam. Three LEDs for wide beam.

Drivers

HPF, electronic, 120-277V (EU-240V).

Minimum Starting Temperature

-25°C (-13°F).


Mechanical

Mounts directly over a standard electrical junction box (by others - North America only). Mounting hardware (by others).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Ext-Wall



SENTI™ - WALL SURFACE EXTERIOR

HOW TO ORDER

A. LUMINAIRE

320201 320201

320211 320211

320241 320241

320221 320221

320231 320231

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FASCIA

ER Elliptical Rings

TB Twin Bars

D. FINISH

MS Silver Metallic

MB Metallic Bronze

F39 Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

E. OPTIONS

PM Perforated Band (applies to middle section only)



SENTI™ - WALL SURFACE EXTERIOR

TECHNICAL DATA

LUMINAIRE

Code	320201	320211	320221	320231	320241
Power (LED)	8W	12W	17W	5W	10W
Beam	Narrow/Narrow	Narrow/Wide	Wide/Wide	Single Narrow	Single Wide




APPROVALS






SENTI™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

100mm/3.9"



222mm/8.75"



191mm/7.5"