

# SENTINEL™ - WALL

Project Name:	Fixture Type:
Fixture Code:	Quantities:



SENTINEL™ - WALL



# SENTINEL™ - WALL

**SENTINEL** stands ready and secures the way, delivering a powerful omnidirectional light reinforced with optional uplight and downlight in either narrow or wide beam angles. Available in 3 styles, **SENTINEL**, **SENTINEL II** or **SENTINEL III**. The use of low copper, die-cast aluminum that is highly resistant to oxidation, stainless steel, and silicone makes this a durable fixture that is built to withstand the elements, especially with the IP65 water and dust ingress rating. Front housing hinges open for access and secures via a bolt hidden behind a spring-loaded flap, allowing for easy maintenance and repair.

## GENERAL SPECIFICATION

### Housing

Die-cast and extruded (low copper) aluminium. Front housing hinges open for access and secures via a bolt hidden behind a spring loaded flap.

### Gaskets

One piece silicone.

### Drivers

HPF electronic, 120-277V, 347V (EU-240V), Dimming for Direct Light Only.

Up/Down light non-dimming.

### Lens

UV stabilised polycarbonate.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

### Approvals

IP65, Wet Location.

### Finish

Exterior grade, metallic powder coated paint.

### Reflector

Aluminium, white powder coated.

### Mechanical

Mounts directly over a standard electrical junction box (by others - North America only).


### Minimum Starting Temperature

-20°C.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Ext-Wall

# SENTINEL™ - WALL

## HOW TO ORDER

### A. LUMINAIRE

<b>ENTE1E01</b> Sentinel	<b>ENTE1E02</b> Sentinel II	<b>ENTE1E03</b> Sentinel III
--------------------------	-----------------------------	------------------------------

### B. FIXTURE LENGTH

<b>FL27</b> 27", 1200 lms	<b>FL51</b> 51", 2400 lms
---------------------------	---------------------------

### C. CRI

<b>CR80</b> CRI 80+
---------------------

### D. VOLTAGE

<b>V1</b> 120/277V	<b>V2</b> 240V <sup>1</sup>
--------------------	-----------------------------

<sup>1</sup> Not available in North America.

### E. DIMMING

<b>DA10</b> 0-10V Dimming 10%
-------------------------------

### F. CCT - FIXTURE FRONT

<b>CTA30</b> 3000K	<b>CTA35</b> 3500K	<b>CTA40</b> 4000K
--------------------	--------------------	--------------------

### G. CCT - DOWNLIGHT MODULE

<b>CTB00</b> Not required	<b>CTB30</b> 3000K	<b>CTB35</b> 3500K	<b>CTB40</b> 4000K
---------------------------	--------------------	--------------------	--------------------

### H. CCT - UPLIGHT MODULE

<b>CTC00</b> Not required	<b>CTC30</b> 3000K	<b>CTC35</b> 3500K	<b>CTC40</b> 4000K
---------------------------	--------------------	--------------------	--------------------

### I. BEAM ANGLE - DOWNLIGHT MODULE

<b>BA00</b> Not require	<b>BA06</b> 6°	<b>BA21</b> 21°
-------------------------	----------------	-----------------

### J. BEAM ANGLE - UPLIGHT MODULE

<b>BB00</b> Not required	<b>BB06</b> 6°	<b>BB21</b> 21°
--------------------------	----------------	-----------------

### K. FINISH

<b>FA02</b> Black Metallic - Textured	<b>FA20</b> Silver Metallic - Textured	<b>FA47</b> Bronze Metallic - Textured
---------------------------------------	--	--

### L. VERTICAL BAR

<b>VB0</b> Not required	<b>VB1</b> Vertical bar, 27" <sup>1</sup>	<b>VB2</b> Vertical bar, 51" <sup>1</sup>
-------------------------	---	---

<sup>1</sup> Available for Sentinel and Sentinel II fascias only.

### M. EMERGENCY

<b>E0</b> Not required	<b>E2</b> Emergency system - Remote <sup>1</sup>
------------------------	--

<sup>1</sup> Front LED only, max distance 10ft, 120/277V).

# SENTINEL™ - WALL

## TECHNICAL DATA

### FIXTURE LENGTH

Code	FL27	FL51
Delivered lms	1200	2400
Wattage	14	28
LPW	86	87

### DOWNLIGHT MODULE BEAM

Code	BA00	BA06	BA21
Delivered Lms Down		150	210
Wattage		2	4
LPW		62	59

### UPLIGHT MODULE BEAM

Code	BB00	BB06	BB21
Delivered lms Up		150	210
Wattage		2	4
LPW		62	59

## LUMINAIRE



Sentinel





Sentinel II



Sentinel III

## FINISH




Black Metallic - Textured   Silver Metallic - Textured   Bronze Metallic - Textured

## APPROVALS





Sentinel 27"



Sentinel 51"

