Fixture Code:	Quantities:	
Project Name:	Fixture Type:	



GENERAL SPECIFICATION

Housing

Die-formed steel.

Perforated accents

Steel, finished as specified.

Front Lens

UV stabilized polycarbonate with vertical ribs.

Upper and lower dust covers

Opal polycarbonate.

Mechanical

Mounts directly to a standard electrical junction box (by others - North America only). Additional mounting points provided. Mounting hardware (by others).

OPTICS & FEATURES



Wall Direct

Horizontal bars

Die-cast zinc.

Finish

Powder coated paint or plated.

Rear Side (Halo) Lens

Extruded opal acrylic.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

HOW TO ORDER

A. LUMINAIRE

326110 326110 **326110 326112** 326112 **326114** 326114 **326116** 326116

326118 326118

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FASCIA

EQ Style EQ **PM** Style PM

D. FINISH

WH WhiteMS Silver MetallicMB Metallic BronzeSN Satin NickelAB Antique BrassPB Polished BrassSB Satin BrassPC Polished Chrome

OT Other painted finish (RAL number

required)

E. OPTIONS

PM Perforated Mesh Accents (PM only) **VB** Vertical Bar (PM only)

TECHNICAL DATA

LUMINAIRE

Code	326110	326112	326114	326116	326118
Power (LED)	14W	20W	28W	47W	59W
Delivered Ims	1311	1865	2592	4333	5523
LPW	93	95	94	92	94
Type (A)	14"	18"	24"		
Type (B)				36"	48"

APPROVALS











