SENTIS™ EQ & PM - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

SENTIS™ EQ & PM - WALL SURFACE

GENERAL SPECIFICATION

Housing
Die-formed steel.

Perforated accents
Steel, finished as specified.

Front Lens
UV stabilized polycarbonate with vertical ribs.

Upper and lower dust covers
Opal polycarbonate.

Mechanical
Mounts directly to a standard electrical junction box (by others - North America only). Additional mounting points provided. Mounting hardware (by others).

Horizontal bars
Die-cast zinc.


Finish
Powder coated paint or plated.

Rear Side (Halo) Lens
Extruded opal acrylic.

Drivers
HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

Delivered Lumens
Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Wall Direct

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

SENTIS™ EQ & PM - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

326110 326110
326112 326112
326114 326114
326116 326116
326118 326118

B. CCT

30 3000K (min 80 CRI)
35 3500K (min 80 CRI)
40 4000K (min 80 CRI)

C. FASCIA

EQ Style EQ
PM Style PM

D. FINISH

WH White
MS Silver Metallic
MB Metallic Bronze
SN Satin Nickel
AB Antique Brass
PB Polished Brass
SB Satin Brass
PC Polished Chrome
OT Other painted finish (RAL number required)

E. OPTIONS

PM Perforated Mesh Accents (PM only)
VB Vertical Bar (PM only)

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

SENTIS™ EQ & PM - WALL SURFACE

TECHNICAL DATA

LUMINAIRE

Code	326110	326112	326114	326116	326118
Power (LED)	14W	20W	28W	47W	59W
Delivered lms	1311	1865	2592	4333	5523
LPW	93	95	94	92	94
Type (A)	14"	18"	24"		
Type (B)				36"	48"

APPROVALS

ADA

© 2026 Beta-Calco Inc. Specifications are subject to change without notice