
Project Name: Fixture Type:

Fixture Code: Quantities:











SENTIS is a robustly designed transitional-style wall sconce, ideally suited for high-traffic zones. Available as a minimalist style with an exposed diffuser or with a decorative and protective grill in 8 finishes.

#### **GENERAL SPECIFICATION**

#### Housing

Die-Formed steel.

#### Perforated accents

Steel, finished as specified.

#### Mechanical

Mounts directly to a standard electrical junction box (by others - North America only). Additional mounting points provided. Mounting hardware (by others).

#### Sensors

Consult factory regarding sensor compatibility.

#### Rear side (halo) diffuser

Extruded opal acrylic.

#### **Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI).

#### **MOUNTING & OPTICS**







Declare

Wall Front/Back

General Diffuse

#### Horizontal bars

Die-cast zinc.

#### **Finish**

Powder coated paint or plated.

#### Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard. The driver is integral to the fixture housing.

#### Front diffuser

UV stabilized polycarbonate with vertical ribs.

#### Upper and lower dust covers

Opal polycarbonate.

#### Approvals

Damp location, (Indoor use only).

### **HOW TO ORDER**

A. LUMINAIRE

**326100** 14", 1311 lms **326102** 18", 1865 lms **326104** 24", 2592 lms **326106** 36", 4333 lms

**326108** 48", 5523 lms

B. CRI

**CR80** CRI 80+ **CR90** CRI 90+

C. CCT

**30** 3000K **35** 3500K **40** 4000K

D. FASCIA

**OP** Style OP **TQ** Style TQ

E. FINISH

WH White MS Silver Metallic Textured BM Bronze Metallic Textured

F. OPTIONS

**PM** Perforated Mesh Accents (TQ only) **VB** Vertical Bar (OP & TQ only)

### **TECHNICAL DATA**

#### **LUMINAIRE**

Code	326100	326102	326104	326106	326108
Power (LED)	14W	20W	28W	47W	59W
Delivered Ims	1311	1865	2592	4333	5523
LPW	93	95	94	92	94
Type (A)	14"	18"	24"		
Type (B)				36"	48"

#### **FINISH**







White

Silver Metallic Textured Bronze Metallic Textured

### **APPROVALS**












### **DIMENSIONAL DIAGRAMS**



Style TQ

Type (A)

Type (B)

100mm/3.9" 191mm/7.5"