

SPECTIVE™ - WALL

Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

SPEW1W Direct

SPEW2W Direct/Indirect

¹ Will consist of two pieces connected. All data based on max values, consult Performance Data download for more details.

B. LENGTH OF RUN

SFA _ _ _ _

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run.

C. FIXTURE LENGTH

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

D. LUMENS/FT DIRECT

LPF020 200 lm/ft

LPF040 400 lm/ft

LPF060 600 lm/ft

E. LUMENS/FT INDIRECT

LPG000 Not required

LPG020 200 lm/ft

LPG040 400 lm/ft

LPG060 600 lm/ft

LPG080 800 lm/ft

LPG100 1000 lm/ft

LPG120 1200 lm/ft

F. CRI

CR90 CRI 90+

G. CCT

CTA30 3000K

CTA35 3500K

CTA40 4000K

H. DIRECT DIFFUSER

DD3 Diffused light diffuser

UPLIGHT DIFFUSER

UD0 Not required

UD2 Opal diffuser

UD3 Asymmetric diffuser ¹

¹ Available up to 1000 lm/ft.

I. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Only available with DA01 dimming.

³ Only available with DA45 dimming.



SPECTIVE™ - WALL

J. DIMMING

DA01 0-10V Dimming 1.0%

DA30 DSI/switchDim²

DA02 0-10V Dimming 0.1%¹

DA45 PoE³

DA20 DALI Dimming 0.1%¹

DA21 DALI Dimming 1.0%¹

¹ Not available with 347V.

² Not available in North America.

³ Only available with V4.

K. FIXTURE FINISH

FA01 White

FA02 Black Metallic Textured

FA20 Silver Metallic Textured

L. INSIDE TRIM FINISH

FB02 Black Metallic Textured

FB20 Silver Metallic Textured

FB59 Gold Anodized

M. EMERGENCY

E0 Not required

E1 Emergency system - Integral¹

¹ Available upon request, consult factory. Not available with V3.

N. CIRCUITS

CS1 Single circuit

CS2 Dual circuit

O. SENSORS



SPECTIVE™ - WALL

DIMENSIONAL DIAGRAMS

Isometric Views

