

# SPECTIVE™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:

## A. LUMINAIRE

**SPEC1P** Direct

**SPEC2P** Direct/Indirect

All data based on max values, consult Performance Data download for more details.  
One power cord for every 50 linear feet.

## B. LENGTH OF RUN

**SFA** \_ \_ \_ \_

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run.

## C. FIXTURE LENGTH

**SL04** 4ft

**SL06** 6ft

**SL08** 8ft

**SL10** 10ft

**SL12** 12ft

## D. LUMENS/FT DIRECT

**LPF020** 200 lm/ft

**LPF040** 400 lm/ft

**LPF060** 600 lm/ft

## E. LUMENS/FT INDIRECT

**LPG000** Not required

**LPG020** 200 lm/ft

**LPG040** 400 lm/ft

**LPG060** 600 lm/ft

**LPG080** 800 lm/ft

**LPG100** 1000 lm/ft

**LPG120** 1200 lm/ft

**LPG140** 1400 lm/ft

## F. CRI

**CR90** CRI 90+

## G. CCT

**CTA30** 3000K

**CTA35** 3500K

**CTA40** 4000K

## H. DIRECT DIFFUSER

**DD3** Diffused light diffuser

## UPLIGHT DIFFUSER

**UD0** Not required

**UD1** Clear diffuser (Batwing distribution) **UD3** Asymmetric diffuser <sup>1</sup>

<sup>1</sup> Available up to 1000 lm/ft.

## UPLIGHT BLACKOUT PLATE

**UB00** Not required

**UB\_ \_** Blackout plate <sup>1</sup>

<sup>1</sup> Available on a per foot basis. May be required to prevent lighting up of duct work in loft type applications.



# SPECTIVE™ - SUSPENDED

## I. VOLTAGE

**V1** 120/277V

**V2** 240V <sup>1</sup>

**V3** 347V <sup>2</sup>

**V4** Low Voltage <sup>3</sup>

<sup>1</sup> Not available in North America.

<sup>2</sup> Only available with DA01 dimming.

<sup>3</sup> Only available with DA45 dimming.

## J. DIMMING

**DA01** 0-10V Dimming 1.0%

**DA02** 0-10V Dimming 0.1% <sup>1</sup>

**DA20** DALI Dimming 0.1% <sup>1</sup>

**DA21** DALI Dimming 1.0% <sup>1</sup>

**DA30** DSI/switchDim <sup>2</sup>

**DA45** PoE <sup>3</sup>

<sup>1</sup> Not available with 347V.

<sup>2</sup> Not available in North America.

<sup>3</sup> Only available with V4.

## K. CEILING TYPE

**H1** Hard ceiling <sup>2</sup>

**H2** Grid ceiling <sup>1</sup>

<sup>1</sup> Combo kit provided includes installation to T-bar and through tile mount.

<sup>2</sup> Designed for drywall ceilings.

## L. SUSPENSION

**HLA03** 3ft cable suspension

**HLA06** 6ft cable suspension

**HLA09** 9ft cable suspension

## M. FIXTURE FINISH

**FA01** White

**FA02** Black Metallic Textured

**FA20** Silver Metallic Textured

## N. INSIDE TRIM FINISH

**FB02** Black Metallic Textured

**FB20** Silver Metallic Textured

**FB59** Gold Anodized

## O. CANOPY FINISH

**CF01** White

**CF02** Black Metallic Textured

**CF20** Silver Metallic Textured

## P. EMERGENCY

**E0** Not required

**E1** Emergency system - Integral <sup>1</sup>

<sup>1</sup> not available with V3.

## Q. CIRCUITS

**CS1** Single circuit


**CS2** Dual circuit

## R. SENSORS




# SPECTIVE™ - SUSPENDED

## DIMENSIONAL DIAGRAMS




Isometric View (Uplight)



Isometric View (Downlight)



Top View (Uplight)



Bottom View (Downlight)