



SPECTIVE™

SHORT SPECIFICATION SHEET



Fixture Type

Fixture Code

Quantities

1 HOW TO ORDER

1. LUMINAIRE

SPEC1P Direct

SPEC2P Direct/Indirect

All data based on max values, consult Performance Data download for more details.
One power cord for every 50 linear feet.

2. LENGTH OF RUN

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run.

SFA _ _ _ _

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run.

3. FIXTURE LENGTH

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

4. LUMENS/FT DIRECT

LPF020 200 lm/ft

LPF040 400 lm/ft

LPF060 600 lm/ft

5. LUMENS/FT INDIRECT

LPG000 Not required

LPG020 200 lm/ft

LPG040 400 lm/ft

LPG060 600 lm/ft

LPG080 800 lm/ft

LPG100 1000 lm/ft

LPG120 1200 lm/ft

LPG140 1400 lm/ft

6. CRI

CR90 CRI 90+

7. CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

8. DIRECT DIFFUSER

DD3 Diffused light diffuser

UPLIGHT DIFFUSER

UD0 Not required

UD1 Clear diffuser (Batwing distribution)

UD3 Asymmetric diffuser ¹

¹ Available up to 1000 lm/ft.

UPLIGHT BLACKOUT PLATE

UB00 Not required

UB_ _ Blackout plate ¹

¹ Available on a per foot basis. May be required to prevent lighting up of duct work in loft type applications.

9. VOLTAGE

V1 120/277V

V2 240V ¹

V3 347V ²

V4 Low Voltage ³

¹ Not available in North America.

² Only available with DA01 dimming.

³ Only available with DA45 dimming.

10. DIMMING

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1% ¹

DA20 DALI Dimming 0.1% ¹

DA21 DALI Dimming 1.0% ¹

DA30 DSI/switchDim ²

DA45 PoE ³

¹ Not available with 347V.

² Not available in North America.

³ Only available with V4.

11. CEILING TYPE

H1 Hard ceiling ²

H2 Grid ceiling ¹

¹ Combo kit provided includes installation to T-bar and through tile mount.

² Designed for drywall ceilings.

12. SUSPENSION

HLA03 3ft cable suspension

HLA06 6ft cable suspension

HLA09 9ft cable suspension

13. FIXTURE FINISH

FA01 White

FA02 Black Metallic Textured

FA20 Silver Metallic Textured

14. INSIDE TRIM FINISH

FB02 Black Metallic Textured

FB20 Silver Metallic Textured

FB59 Gold Anodized

15. CANOPY FINISH

CF01 White

CF02 Black Metallic Textured

CF20 Silver Metallic Textured

16. EMERGENCY

E0 Not required

E1 Emergency system – Integral ¹

¹ not available with V3.

17. CIRCUITS

CS1 Single circuit

CS2 Dual circuit

18. SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.