





# SPECTIVE™


## SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

### 1 HOW TO ORDER

#### 1. LUMINAIRE

**SPEC1P** Direct

**SPEC2P** Direct/Indirect

All data based on max values, consult Performance Data download for more details. One power cord for every 50 linear feet.

#### 2. LENGTH OF RUN

Length of run is 4', 6', 8', 10' or 12' only, not available as a continuous run.

SFA\_ \_ \_ \_

#### 3. FIXTURE LENGTH

**SL04** 4ft

**SL06** 6ft

**SL08** 8ft

**SL10** 10ft

**SL12** 12ft

#### 4. LUMENS/FT DIRECT

**LPF020** 200 lm/ft

**LPF040** 400 lm/ft

**LPF060** 600 lm/ft

#### 5. LUMENS/FT INDIRECT

**LPG000** Not required

**LPG020** 200 lm/ft

**LPG040** 400 lm/ft

**LPG060** 600 lm/ft

**LPG080** 800 lm/ft

**LPG100** 1000 lm/ft

**LPG120** 1200 lm/ft

**LPG140** 1400 lm/ft

## 6. CRI

**CR90** CRI 90+

## 7. CCT

**CTA27** 2700K

**CTA30** 3000K

**CTA35** 3500K

**CTA40** 4000K

**CTA60** Tunable White <sup>1</sup>

<sup>1</sup> Consult factory.

## 8. DIRECT LENS

**DD3** Diffused Light

## 9. INDIRECT LENS

**UD0** Not required

**UD1** Clear (Batwing Distribution)

**UD3** Asymmetric <sup>1</sup>

<sup>1</sup> Available up to 1000 lm/ft.

## 10. INDIRECT BLACKOUT PLATE

**UB00** Not required

**UB\_ \_** Blackout plate <sup>1</sup>

<sup>1</sup> Available on a per foot basis. May be required to prevent lighting up of duct work in loft type applications.

## 11. VOLTAGE

**V1** 120/277V

**V2** 240V <sup>1</sup>

**V3** 347V <sup>2</sup>

**V4** Low Voltage <sup>3</sup>

<sup>1</sup> Not available in North America. <sup>2</sup> Only available with DA01 dimming. <sup>3</sup> Only available with DA45 dimming.

## 12. DIMMING

**DA01** 0-10V Dimming 1.0%

**DA02** 0-10V Dimming 0.1% <sup>1</sup>

**DA20** DALI Dimming 0.1% <sup>1</sup>

**DA21** DALI Dimming 1.0% <sup>1</sup>

**DA30** DSI/switchDim <sup>2</sup>

**DA45** PoE <sup>3</sup>

<sup>1</sup> Not available with 347V. <sup>2</sup> Not available in North America. <sup>3</sup> Only available with V4.

### 13. CEILING TYPE

**H1** Hard ceiling <sup>2</sup>

**G1** Grid ceiling <sup>1</sup>

<sup>1</sup> Combo kit provided includes installation to T-bar and through tile mount. <sup>2</sup> Designed for drywall ceilings.

### 14. SUSPENSION

**HLA03** 3ft cable suspension

**HLA06** 6ft cable suspension

**HLA09** 9ft cable suspension

### 15. FIXTURE FINISH

**FA01** White

**FA02** Black Metallic Textured

**FA20** Silver Metallic Textured

### 16. INSIDE TRIM FINISH

**FB02** Black Metallic Textured

**FB20** Silver Metallic Textured

**FB59** Gold Anodized

### 17. CANOPY FINISH

**CF01** White

**CF02** Black Metallic Textured

**CF20** Silver Metallic Textured

### 18. EMERGENCY

**E0** Not required

**E1** Emergency system – Integral <sup>1</sup>

<sup>1</sup> Not available with V3.

### 19. CIRCUITS

**CS1** Single circuit

**CS2** Dual circuit

### 20. SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.