



SPECTIVE™

SHORT SPECIFICATION SHEET



Fixture Type

Fixture Code

Quantities

1 HOW TO ORDER

1. LUMINAIRE

SPEC1P Direct

SPEC2P Direct/Indirect

All data based on max values, consult Performance Data download for more details.

One power cord for every 50 linear feet.

2. LENGTH OF RUN

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run.

SFA _ _ _ _

Length of run is 4, 6, 8, 10 or 12ft only, not available as a continuous run.

3. FIXTURE LENGTH

SL04 4ft

SL06 6ft

SL08 8ft

SL10 10ft

SL12 12ft

4. LUMENS/FT DIRECT

LPF020 200 lm/ft

LPF040 400 lm/ft

LPF060 600 lm/ft

5. LUMENS/FT INDIRECT

LPG000 Not required

LPG020 200 lm/ft

LPG040 400 lm/ft

LPG060 600 lm/ft

LPG080 800 lm/ft

LPG100 1000 lm/ft

LPG120 1200 lm/ft

LPG140 1400 lm/ft

6. CRI

CR90 CRI 90+

7. CCT

CTA27 2700K

CTA30 3000K

CTA35 3500K

CTA40 4000K

CTA60 Tunable White ¹

¹ Consult factory.

8. DIRECT LENS

DD3 Diffused Light

INDIRECT LENS

UD0 Not required **UD1** Clear (Batwing Distribution) **UD3** Asymmetric ¹

¹ Available up to 1000 lm/ft.

INDIRECT BLACKOUT PLATE

UB00 Not required **UB_ _** Blackout plate ¹

¹ Available on a per foot basis. May be required to prevent lighting up of duct work in loft type applications.

9. VOLTAGE

V1 120/277V **V2** 240V ¹ **V3** 347V ² **V4** Low Voltage ³

¹ Not available in North America.

² Only available with DA01 dimming.

³ Only available with DA45 dimming.

10. DIMMING

DA01 0–10V Dimming 1.0% **DA02** 0–10V Dimming 0.1% ¹ **DA20** DALI Dimming 0.1% ¹ **DA21** DALI Dimming 1.0% ¹
DA30 DSI/switchDim ² **DA45** PoE ³

¹ Not available with 347V.

² Not available in North America.

³ Only available with V4.

11. CEILING TYPE

H1 Hard ceiling ² **G1** Grid ceiling ¹

¹ Combo kit provided includes installation to T-bar and through tile mount.

² Designed for drywall ceilings.

12. SUSPENSION

HLA03 3ft cable suspension **HLA06** 6ft cable suspension **HLA09** 9ft cable suspension

13. FIXTURE FINISH

FA01 White **FA02** Black Metallic Textured **FA20** Silver Metallic Textured

14. INSIDE TRIM FINISH

FB02 Black Metallic Textured **FB20** Silver Metallic Textured **FB59** Gold Anodized

15. CANOPY FINISH

CF01 White **CF02** Black Metallic Textured **CF20** Silver Metallic Textured

16. EMERGENCY

E0 Not required **E1** Emergency system – Integral ¹

¹ not available with V3.

17. CIRCUITS

CS1 Single circuit **CS2** Dual circuit

18. SENSORS

Compatible with Avi-On, Casambi, Enlighted, Lutron Vive, nLight, NX Lighting Controls, Osram, Philips, and others. Consult factory.