



# STEP™

## FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE




QUANTITIES

### 1 DESCRIPTION

**STEP** is designed to blend into the architecture while illuminating steps and pathways. With asymmetric light distribution, **STEP** makes efficient use of the light output directing it to exactly where it is required. Available in 3 polyester-based finishes, this fixture is both Dark Sky (for the 3000K variant) and Turtle friendly, with the amber LED also available. The use of low copper, die-cast aluminum that is highly resistant to oxidation, stainless steel, tempered glass, and silicone makes this a durable fixture that is built to withstand the elements, especially with the IP66 water and dust ingress rating.

### 2 OPTICS & FEATURES



Ext-Wall  
Recessed  
Downlight



Dark Sky  
Friendly

### 3 APPROVALS



IP66

### 4 GENERAL SPECIFICATION

#### HOUSING

Low copper, die-cast aluminum highly resistant to oxidation.

#### FINISH

Powder coated.

**LENS**

4mm/0.2" tempered glass.

**CABLE ENTRY**

Double silicon gland for DIA 10–14mm/0.4–0.5" cables.

**DRIVERS**

HPF, electronic 120–277V.

**EXTERNAL SCREWS**

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

**DELIVERED LUMENS**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**SUSTAINABILITY**

Designed for on-site LED board, driver, and optic replacement.  
Contact the factory for maintenance documentation.

**GASKET**

Silicone.

**REFLECTORS**

High purity aluminum.

**ROUGH-IN HOUSING**

Thermoplastic.

**MECHANICAL**

For wall installation in poured concrete/brick.

**DARK SKY FRIENDLY**

Dark Sky Friendly if ordered with 3000K CCT.

**5 DESIGN OPTIONS**

**FINISH**



Black  
Metallic  
Textured

Anthracite  
Gray

Light Gray

**6 HOW TO ORDER**

**1. LUMINAIRE**

**8207610** 6W, 21 lms

**2. CCT**

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

**TF** Amber LED (Turtle Friendly)

**3. FINISH**

**BL** Black Metallic Textured

**AG** Anthracite Gray

**GR** Light Gray

#### 4. DIMMING

DB Dimming (0-10V, 10%) <sup>1</sup>

<sup>1</sup> Dimming is equal to or less than 10%.

#### 5. ROUGH-IN HOUSING (REQUIRED)

RIH6503 Rough-In Housing

### 7 TECHNICAL DATA

#### LUMINAIRE

Code	8207610
Power (LED)	6W
Delivered lms	21

### 8 DIMENSIONAL DIAGRAMS

