





# STEP™


## FULL SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE




QUANTITIES

### 1 DESCRIPTION

**STEP** is designed to blend into the architecture while illuminating steps and pathways. With asymmetric light distribution, **STEP** makes efficient use of the light output directing it to exactly where it is required. Available in 3 polyester-based finishes, this fixture is both Dark Sky (for the 3000K variant) and Turtle friendly, with the amber LED also available. The use of low copper, die-cast aluminum that is highly resistant to oxidation, stainless steel, tempered glass, and silicone makes this a durable fixture that is built to withstand the elements, especially with the IP66 water and dust ingress rating.

### 2 OPTICS & FEATURES



Ext-Wall  
Recessed  
Downlight



Dark Sky  
Friendly

### 3 APPROVALS



IP66

### 4 GENERAL SPECIFICATION

#### HOUSING

Low copper, die-cast aluminum highly resistant to oxidation.

#### FINISH

Powder coated.

**LENS**

4mm/0.2" tempered glass.

**CABLE ENTRY**

Double silicon gland for DIA 10–14mm/0.4–0.5" cables.

**DRIVERS**

HPF, electronic 120–277V.

**EXTERNAL SCREWS**

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

**DELIVERED LUMENS**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**SUSTAINABILITY**

Designed for on-site LED board, driver, and optic replacement.  
Contact the factory for maintenance documentation.

**GASKET**

Silicone.

**REFLECTORS**

High purity aluminum.

**ROUGH-IN HOUSING**

Thermoplastic.

**MECHANICAL**

For wall installation in poured concrete/brick.

**DARK SKY FRIENDLY**

Dark Sky Friendly if ordered with 3000K CCT.

**5 DESIGN OPTIONS**

**FINISH**



Black  
Metallic  
Textured

Anthracite  
Gray

Light Gray

**6 HOW TO ORDER**

<p><b>LUMINAIRE</b></p> <p><b>8207610</b> 6W, 21 lms</p>	<p><b>CCT</b></p> <p><b>30</b> 3000K (min 80 CRI) <b>40</b> 4000K (min 80 CRI) <b>TF</b> Amber LED (Turtle Friendly)</p>	<p><b>FINISH</b></p> <p><b>BL</b> Black Metallic Textured <b>AG</b> Anthracite Gray <b>GR</b> Light Gray</p>	<p><b>DIMMING</b></p> <p><b>DB</b> Dimming (0–10V, 10%)<sup>1</sup></p> <p><sup>1</sup> Dimming is equal to or less than 10%.</p>
<p><b>ROUGH-IN HOUSING (REQUIRED)</b></p> <p><b>RIH6503</b> Rough-In Housing</p>			

**7** TECHNICAL DATA

**LUMINAIRE**

<b>Code</b>	<b>8207610</b>
<b>Power (LED)</b>	6W
<b>Delivered lms</b>	21

**8** DIMENSIONAL DIAGRAMS

