



# STEP™

## FULL SPECIFICATION SHEET



Fixture Type

Fixture Code

Quantities

### 1 DESCRIPTION

**STEP** is designed to blend into the architecture while illuminating steps and pathways. With asymmetric light distribution, Step makes efficient use of the light output directing it to exactly where it is required. Available in 3 polyester-based finishes, as well as Turtle-friendly, amber LED.

### 2 OPTICS & FEATURES



Ext-Wall  
Recessed  
Downlight



Dark Sky  
Friendly

### 3 APPROVALS



4 GENERAL SPECIFICATION

**HOUSING**

Low copper, die-cast aluminum highly resistant to oxidation.

**DIFFUSER**

4mm/0.2" tempered glass.

**CABLE ENTRY**

Double silicon gland for DIA 10-14mm/0.4-0.5" cables.

**DRIVERS**

HPF, electronic 120-277V.

**EXTERNAL SCREWS**

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

**DELIVERED LUMENS**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**FINISH**

Powder coated.

**GASKET**

Silicone.

**REFLECTORS**

High purity aluminum.

**ROUGH-IN HOUSING**

Thermoplastic.

**MECHANICAL**

For wall installation in poured concrete/brick.

**DARK SKY FRIENDLY**

Dark Sky Friendly if ordered with 3000K CCT.

## 5 DESIGN OPTIONS

### FINISH



Black  
Metallic  
Textured



Anthracite  
Gray



Light Gray

## 6 HOW TO ORDER

### 1. LUMINAIRE

**8207610** 6W, 21 lms

### 2. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

**TF** Amber LED (Turtle Friendly)

### 3. FINISH

**BL** Black Metallic Textured

**AG** Anthracite Gray

**GR** Light Gray

### 4. DIMMING

**DB** Dimming (0-10V, 10%) <sup>1</sup>

<sup>1</sup> Dimming is equal to or less than 10%.

### 5. ROUGH-IN HOUSING (REQUIRED)

**RIH6503** Rough-In Housing

## 7 TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>8207610</b>
<b>Power (LED)</b>	6W
<b>Delivered lms</b>	21

8 DIMENSIONAL DIAGRAMS

