Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Steel and extruded aluminum.

Lens

Opal acrylic.

Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V dimming standard (10%).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Wall Front/Back

Finish

Back plate, powder coated gloss white. Side trim, powder coated gloss white. Cover, finished as listed.

Dust covers

Opal Polycarbonate.

Mechanical

Luminaires mount directly to a junction box.

HOW TO ORDER

A. LUMINAIRE

411701 411701 **411713** 411713

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

C. COVER FINISH

WH White MS Silver Metallic **AB** Antique brass **SB** Satin brass

SN Satin nickel **OT** Other painted finish (RAL number

required) (sample chip required)

F40 Other Non-RAL painted finish

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	411701	411713
Power (LED)	15W	21W
Delivered Ims	1202	1714
LPW	82	82
Weight	4.4lb	4.4lb

APPROVALS













DIMENSIONAL DIAGRAMS

