

# SURA OP™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# SURA OP™ - WALL SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and extruded aluminum.

### Diffuser

Opal acrylic.

### Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V dimming standard (10%).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Finish

Back plate, powder coated gloss white. Side trim, powder coated gloss white.  
Cover, finished as listed.


### Dust covers

Opal Polycarbonate.

### Mechanical

Luminaires mount directly to a junction box.

## MOUNTING & OPTICS



Wall Front/Back

# SURA OP™ - WALL SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**411701** 411701

**411713** 411713

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. COVER FINISH

**WH** White

**MS** Silver Metallic

**AB** Antique brass

**SB** Satin brass

**SN** Satin nickel

**OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	<b>411701</b>	<b>411713</b>
Power (LED)	15W	21W
Delivered lms	1202	1714
LPW	82	82
Weight	4.4lb	4.4lb

## APPROVALS

ADA



CE



IP20



# SURA OP™ - WALL SURFACE

## DIMENSIONAL DIAGRAMS

