

SURA OP™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 4

SURA OP™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and extruded aluminum.

Finish

Back plate, powder coated gloss white. Side trim, powder coated gloss white. Cover, finished as listed.

Lens

Opal acrylic.

Dust covers

Opal Polycarbonate.

Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V dimming standard (10%).


Mechanical

Luminaires mount directly to a junction box.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Wall Front/Back



SURA OP™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

411701 411701

411713 411713

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. COVER FINISH

WH White

MS Silver Metallic

AB Antique brass

SB Satin brass

SN Satin nickel

OT Other painted finish (RAL number required)

F40 Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	411701	411713
Power (LED)	15W	21W
Delivered lms	1202	1714
LPW	82	82
Weight	4.4lb	4.4lb

APPROVALS



SURA OP™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

