

# TATTO™ - INGROUND EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# TATTO™ - INGROUND EXTERIOR

## GENERAL SPECIFICATION

### Housing

Low copper, die-cast aluminum highly resistant to oxidation.

### Bezel

Stainless steel or trimless glass.

### Finish

Double powder coating polyester high resistant to UV and oxidation.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

### Drivers

HPF, electronic for 120-277V. Dimming 0-10V.

### Rough-in housing

Thermoplastic.

### Lens

10mm/0.39" tempered glass (12mm/0.47" stainless steel version), Type B 15mm/0.59". IK 07 Mechanical resistant 2 Joule.

### Gasket

Silicone.

### Reflectors

High purity aluminum.

### Cable entry

M20 cable gland for DIA 6-12mm/0.24-0.47" cables.

### Walk over

Static pressure load 500Kg/1100lbs.

### Mechanical

For in-ground installation in poured concrete.

## OPTICS & FEATURES



Ext-Inground

# TATTO™ - INGROUND EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**8107050** 8107050  
**8107070** 8107070

**8107052** 8107052  
**8107072** 8107072

**8107054** 8107054  
**8107074** 8107074

**8107056** 8107056  
**8107076** 8107076

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. OPTIONS

**AS** Anti-Slip Glass

**DB** Dimming (0-10V, 10%)

### D. ROUGH-IN HOUSING (REQUIRED)

**RIH1720** Rough-In Housing for Type A - Glass Bezel

**RIH1721** Rough-In Housing for Type B - Stainless Steel Bezel

## TECHNICAL DATA

### LUMINAIRE

<b>Code</b>	<b>8107050</b>	<b>8107052</b>	<b>8107054</b>	<b>8107056</b>	<b>8107070</b>	<b>8107072</b>
<b>Power (LED)</b>	22W	39W	39W	39W	22W	39W
<b>Distribution</b>	Spot 13	Asymmetric 48	10 Spot	71 Flood	Spot 13	Asymmetric 48
<b>Delivered lms</b>	2752	3326	4062	3505	2752	3326
<b>Type</b>	A	A	A	A	B	B
<b>Code</b>	<b>8107074</b>	<b>8107076</b>				
<b>Power (LED)</b>	39W	39W				
<b>Distribution</b>	10 Spot	71 Flood				
<b>Delivered lms</b>	4062	3505				
<b>Type</b>	B	B				

## APPROVALS



IP67



# TATTO™ - INGROUND EXTERIOR

## DIMENSIONAL DIAGRAMS

