

TIMPANI RD™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

TMRC1C01 18", 3200 lms

TMRC1C02 24", 5300 lms

TMRC1C03 36", 13000 lms

TMRC1C04 48", 24000 lms

B. LUMENS

LMA0170 1700 lms

LMA0250 2500 lms

LMA0320 3200 lms

LMA0420 4200 lms

LMA0530 5300 lms

LMA0730 7300 lms

LMA1060 10600 lms

LMA1300 13000 lms

LMA1900 19000 lms

LMA2400 24000 lms

Consult website for lumens by size.

C. CRI

CR80 CRI 80+

D. CCT

CTA30 3000K

CTA35 3500K

CTA40 4000K

E. VOLTAGE

V1 120/277V

V2 240V¹

V3 347V²

V4 Low Voltage³

¹ Not available in North America.

² Only available with DA01 dimming.

³ Only available with DA45 dimming.

F. DIMMING OPTIONS

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1%^{1 3}

DA21 DALI Dimming 1.0%^{1 3}

DA30 DSI/switchDim^{2 3}

DA45 PoE *

¹ Available with 18" & 24" diameters only.

² Not available in North America.

³ Not available with V3.

* Only available with V4.

G. FINISH

FA01 White

FA02 Black Metallic - Textured

FA20 Silver Metallic - Textured

FA44 Midnight Blue Metallic - Textured

FA25 Gold Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

Other finishes available, consult factory.

H. EMERGENCY

E0 Not required

E1 Emergency system - Integral



TIMPANI RD™ - CEILING

DIMENSIONAL DIAGRAMS

