

TIMPANI SQ™ - CEILING



Project Name:

Fixture Type:

Fixture Code:

Quantities:

A. LUMINAIRE

973320 24", 4991 lms

973330 36", 13279 lms

973340 48", 25532 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

WH White

BL Black Metallic Textured

MS Silver Metallic Textured

FA44 Midnight Blue Metallic - Textured

FA25 Gold Metallic - Textured

FA45 Copper Metallic

FA46 Charcoal Metallic - Textured

FA47 Bronze Metallic - Textured

FA52 Champagne Metallic

FA53 Red Metallic - Textured

D. LUMEN & WATTAGE REDUCTION

PRO Lumen & Wattage Reduction to approximately 25% of standard output

PR1 Lumen & Wattage Reduction to approximately 50% of standard output

PR2 Lumen Wattage & Reduction to approximately 75% of standard output

Note: Custom Reduction Percentages Available Upon Request.

E. DIMMING OPTIONS

D1 0-10V Dimming (1%)

D2 0-10V Dimming 0.1% ¹

DL DALI Dimming (1%)

DS DSI (EU only) ²

SD SwitchDim (EU only) ²

DE PoE ³

0-10V, 1% dimming standard.

¹ available with 24" (610mm) diameters only.

² DS & SD options not available in North America.

³ DE must be used with EV only.

F. OPTIONAL LOW VOLTAGE

EV Low Voltage

To be used with DE only.



TIMPANI SQ™ - CEILING

DIMENSIONAL DIAGRAMS

