

TIMPANI SQ™ - CEILING



Project Name:	Fixture Type:
Fixture Code:	Quantities:

A. LUMINAIRE

973320 24", 4991 lms	973330 36", 13279 lms	973340 48", 25532 lms
-----------------------------	------------------------------	------------------------------

B. CCT

30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------	------------------------------

C. FINISH

WH White	BL Black Metallic Textured	MS Silver Metallic Textured	FA44 Midnight Blue Metallic - Textured
FA25 Gold Metallic - Textured	FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured
FA52 Champagne Metallic	FA53 Red Metallic - Textured		

D. LUMEN & WATTAGE REDUCTION

PRO Lumen & Wattage Reduction to approximately 25% of standard output	PR1 Lumen & Wattage Reduction to approximately 50% of standard output	PR2 Lumen Wattage & Reduction to approximately 75% of standard output
--	--	--

Note: Custom Reduction Percentages Available Upon Request.

E. DIMMING OPTIONS

D1 0-10V Dimming (1%)	D2 0-10V Dimming 0.1% ¹	DL DALI Dimming (1%)	DS DSI (EU only) ²
SD SwitchDim (EU only) ²	DE PoE ³		

0-10V, 1% dimming standard.
¹ available with 24" (610mm) diameters only.
² DS & SD options not available in North America.
³ DE must be used with EV only.

F. OPTIONAL LOW VOLTAGE

EV Low Voltage

To be used with DE only.

TIMPANI SQ™ - CEILING

DIMENSIONAL DIAGRAMS

